















**EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.**

**BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.**










Lithium based (LiPo) batteries detailed below, are approved for various EFRA Electric Classes. Section Rules will detail the type applicable. EFRA rules limit battery energy capacity to comply with Airline Requirements (currently 100Wh.), based on Manufacturers data below. Batteries approved from 2011 onwards must comply with the weight range specified. Batteries factory sealed (glue, weld etc.). Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed. **Manufacturers advise that charge rate be restricted to 1C for optimum lifespan, but should not be more than stated below (for 2017 on). Batteries MUST be charged using a 2S LiPo compatible charger. LiPo 'Sack' must be used when charging or discharging prior to race. It is strictly NOT ALLOWED, to charge 2S LiPo Batteries to give an output voltage exceeding 8.40v.**

Submitted by:	Label Details Part #	Illustration only	Manufacturer Supplied Data.	EFRA measured Specification,	Approval Date
<b>BATTERIES ON THIS LIST WERE APPROVED BY EFRA IN YEARS 2014 - 2019 AND ARE ALLOWED AT 2024 EVENTS.</b>					
Associated Electrics	Reedy Zappers SG2 # 27338		Reedy LiPo 2S 7.6v. 32.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 154.9 g. Allowed: 149/161 g.	16.01.19
Associated Electrics	Reedy Zappers SG2 # 27336		Reedy LiPo 2S 7.6v. 45.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.1 g. Allowed: 207/225 g.	16.01.19
Associated Electrics	Reedy Zappers SG2 # 27334		Reedy LiPo 2S 7.6v. 46.0 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 265.9 g. Allowed: 259/281 g.	16.01.19
Team Corally	Corally Voltax # 49601		Corally LiPo 2S 7.6v. 30.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 155.8 g. Allowed: 149/161 g.	16.01.19
Freemax Technology	Arrowmax # AM 700712		Arrowmax LiPo 2S 7.4v. 38.5 Wh. 110C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 231.5 g. Allowed: 224/242 g.	16.01.19
Freemax Technology	Arrowmax # AM 700707		Arrowmax LiPo 2S 7.4v. 45.9 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 288.9 g. Allowed: 276/300 g.	16.01.19
Graupner	Gaupner # 78146.2		Graupner LiPo 2S 7.4v. 34.0 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 213.2 g. Allowed: 207/225 g.	16.01.19
Graupner	Gaupner # 78149.2		Graupner LiPo 2S 7.4v. 37.0 Wh. 150C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 222.1 g. Allowed: 212/230 g.	16.01.19
Graupner	Gaupner # 78150.2		Graupner LiPo 2S 7.4v. 37.0 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 264.1 g. Allowed: 248/268 g.	16.01.19
Graupner	Gaupner # 78172.2		Graupner LiPo 2S 7.4v. 53.3 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 310.6 g. Allowed: 299/323 g.	16.01.19

Graupner	Gaupner # 78180.2		Graupner LiPo 2S 7.4v. 59.2 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 320.6 g. Allowed: 312/338 g.	16.01.19
Graupner	Gaupner # 78181.2		Graupner LiPo 2S 7.4v. 60.0 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 325.4 g. Allowed: 312/338 g.	16.01.19
Intellect Battery	IP # LP2S3600HV4		Intellect LiPo 2S 7.6v. 27.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 155.7 g. Allowed: 149/161 g.	16.01.19
Intellect Battery	IP # LP2S4200HV4		Intellect LiPo 2S 7.6v. 32.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 155.2 g. Allowed: 149/161 g.	16.01.19
Intellect Battery	IP # BG2S5000HV4		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 205.1 g. Allowed: 197/213 g.	16.01.19
Intellect Battery	IP # BG2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.4 g. Allowed: 207/225 g.	16.01.19
Intellect Battery	IP # CC2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 267.3 g. Allowed: 259/281 g.	16.01.19
Intellect Battery	IP # CC2S7000HV4		Intellect LiPo 2S 7.6v. 53.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 271.5 g. Allowed: 259/281 g.	16.01.19
Intellect Battery	IP # CC2S7600HV4		Intellect LiPo 2S 7.6v. 58.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 308.1 g. Allowed: 293/317 g.	16.01.19
Intellect Battery	IP # CC2S8400HV4		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 334.4 g. Allowed: 317/343 g.	16.01.19
LRP	LRP Stock Spec # 430287		LRP LiPo 2S 7.6v. 26.6 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 156.8 g. Allowed: 149/161 g.	16.01.19
LRP	LRP G3 Modified # 430273		LRP LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 157.2 g. Allowed: 149/161 g.	16.01.19
LRP	LRP G3 Stock Spec # 430275		LRP LiPo 2S 7.6v. 30.4 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 187.1 g. Allowed: 182/198 g.	16.01.19
LRP	LRP G3 Modified # 430286		LRP LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 181.2 g. Allowed: 175/189 g.	16.01.19

LRP	LRP G3 Stock Spec # 430284		LRP LiPo 2S 7.6v. 36.5 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 208.0 g. Allowed: 202/218 g.	16.01.19
LRP	LRP G3 Stock spec # 430285		LRP LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 221.3 g. Allowed: 211/229 g.	16.01.19
LRP	LRP G3 Modified # 430272		LRP LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.1 g. Allowed: 206/224 g.	16.01.19
LRP	LRP G3 Modified # 430282		LRP LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 233.4 g. Allowed: 221/239 g.	16.01.19
LRP	LRP G3 Stock spec # 430281		LRP LiPo 2S 7.6v. 45.6 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 269.4 g. Allowed: 259/281 g.	16.01.19
LRP	LRP G3 Modified # 430271		LRP LiPo 2S 7.6v. 48.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 275.6 g. Allowed: 263/285 g.	16.01.19
LRP	LRP G3 Stock spec # 430276		LRP LiPo 2S 7.6v. 55.5 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 305.4 g. Allowed: 292/316 g.	16.01.19
LRP	LRP G3 Stock spec # 430280		LRP LiPo 2S 7.6v. 60.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 332.3 g. Allowed: 319/345 g.	16.01.19
Modern Creations	T/Silverback Siren-HV # HV4600 1302SC-96		Modern Creations LiPo 2S 7.6v. 35.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 191.7 g. Allowed: 186/202 g.	16.01.19
Modern Creations	T/Silverback Siren-HV # HV5500 1302SIND		Modern Creations LiPo 2S 7.6v. 41.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 233.4 g. Allowed: 226/244 g.	16.01.19
Modern Creations	T/Silverback Spiral-IV # 6300 1202SINC		Modern Creations LiPo 2S 7.4v. 46.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 268.8 g. Allowed: 259/281 g.	16.01.19
Muchmore Racing	Impact # MLSG- STLCGHV3800		Muchmore LiPo 2S 7.6v. 28.9 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 186.5 g. Allowed: 181/197 g.	16.01.19
Muchmore Racing	Impact # MLSG- STLCGMP4400		Muchmore LiPo 2S 7.4v. 32.6 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 186.3 g. Allowed: 183/199 g.	16.01.19
Muchmore Racing	Impact # MLSG- STLCGHV4500		Muchmore LiPo 2S 7.6v. 34.2 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 185.9 g. Allowed: 185/201 g.	16.01.19

Muchmore Racing	Impact # MLSG-SLCGHV5500		Muchmore LiPo 2S 7.6v. 41.8 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 235.1 g. Allowed: 226/244 g.	16.01.19
Muchmore Racing	Impact # MLSG-LCGMP6000		Muchmore LiPo 2S 7.4v. 44.4 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 290.1 g. Allowed: 276/300 g.	16.01.19
Muchmore Racing	Impact # MLSG-SLCGHV6000		Muchmore LiPo 2S 7.6v. 45.6 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 282.9 g. Allowed: 270/292 g.	16.01.19
Muchmore Racing	Impact # MLSG-MP82000		Muchmore LiPo 2S 7.4v. 60.7 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 326.6 g. Allowed: 310/336 g.	16.01.19
Nosram	Nosram G3 Modified # 999553		Nosram LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 157.7 g. Allowed: 149/161 g.	16.01.19
Nosram	Nosram G3 Modified # 999560		Nosram LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 181.5 g. Allowed: 175/189 g.	16.01.19
Nosram	Nosram G3 Stock Spec # 999559		Nosram LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.9 g. Allowed: 211/229 g.	16.01.19
Nosram	Nosram G3 Modified # 999558		Nosram LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 233.2 g. Allowed: 221/239 g.	16.01.19
Nosram	Nosram G3 Stock Spec # 999557		Nosram LiPo 2S 7.6v. 48.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.1 g. Allowed: 263/285 g.	16.01.19
Nosram	Nosram G3 Stock Spec # 999552		Nosram LiPo 2S 7.6v. 55.5 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 308.8 g. Allowed: 292/316 g.	16.01.19
Nosram	Nosram G3 Stock Spec # 999556		Nosram LiPo 2S 7.6v. 60.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 333.4 g. Allowed: 317/343 g.	16.01.19
Neidhart SA	Performa # PA9304		Neidhart SA LiPo 2S 7.4v. 27.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 125.7 g. Allowed: 124/134 g.	16.01.19
Neidhart SA	Performa # PA9305		Neidhart SA LiPo 2S 7.6v. 30.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 127.4 g. Allowed: 126/136 g.	16.01.19
Neidhart SA	Performa # PA9306		Neidhart SA LiPo 2S 7.4v. 43.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.4 g. Allowed: 202/218 g.	16.01.19












Neidhart SA	Performa # PA9307		Neidhart SA LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 207.3 g. Allowed: 204/222 g.	16.01.19
PK Racing	PK Racing Ashira # PK-200-116		PK Racing LiPo 2S 7.6v. 42.6 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 211.7 g. Allowed: 209/227 g.	16.01.19
PK Racing	PK Racing Ashira # PK-200-118		PK Racing LiPo 2S 7.6v. 45.6 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 260.4 g. Allowed: 254/276 g.	16.01.19
PK Racing	PK Racing Ashira # PK-200-120		PK Racing LiPo 2S 7.6v. 60.8 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 313.8 g. Allowed: 303/329 g.	16.01.19
PK Racing	PK Racing Asuga # PK-200-008		PK Racing LiPo 2S 7.6v. 30.4 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 153.3 g. Allowed: 149/161 g.	16.01.19
PK Racing	PK Racing Asuga # PK-200-010		PK Racing LiPo 2S 7.6v. 45.6 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.6 g. Allowed: 207/225 g.	16.01.19
PK Racing	PK Racing Asuga # PK-200-018		PK Racing LiPo 2S 7.6v. 51.7 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 270.9 g. Allowed: 259/281 g.	16.01.19
PK Racing	PK Racing Asuga # PK-200-020		PK Racing LiPo 2S 7.6v. 62.3 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 333.4 g. Allowed: 317/343 g.	16.01.19
PK Racing	PK Racing Kansan # PK-200-214		PK Racing LiPo 2S 7.6v. 39.5 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 208.3 g. Allowed: 200/216 g.	16.01.19
PK Racing	PK Racing Kansan # PK-200-216		PK Racing LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.4 g. Allowed: 209/227 g.	16.01.19
PK Racing	PK Racing Kansan # PK-200-218		PK Racing LiPo 2S 7.6v. 48.6 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 261.4 g. Allowed: 256/278 g.	16.01.19
PK Racing	PK Racing Kansan # PK-200-220		PK Racing LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 303.1 g. Allowed: 300/324 g.	16.01.19
PK Racing	PK Racing Sketer # PK-200-258		PK Racing LiPo 2S 7.4v. 37.0 Wh. 150C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 221.8 g. Allowed: 207/225 g.	16.01.19
PK Racing	PK Racing Sketer # PK-200-260		PK Racing LiPo 2S 7.4v. 44.4 Wh. 150C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 270.2 g. Allowed: 259/281 g.	16.01.19

PK Racing	PK Racing Sketer # PK-200-262		PK Racing LiPo 2S 7.4v. 59.2 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 326.9 g. Allowed: 313/339 g.	16.01.19
Process Measurement & Analysis	Optipower # OPR 28002S100B		Optipower LiPo 2S 7.4v. 20.7 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 130.1 g. Allowed: 124/134 g.	16.01.19
Process Measurement & Analysis	Optipower # OPR 33002S100B		Optipower LiPo 2S 7.4v. 24.4 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 149.5 g. Allowed: 141/153 g.	16.01.19
Process Measurement & Analysis	Optipower # OPR 58002S100B		Optipower LiPo 2S 7.4v. 42.9 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 282.0 g. Allowed: 269/291 g.	16.01.19
Process Measurement & Analysis	Optipower # OPR 85002S100B		Optipower LiPo 2S 7.4v. 62.9 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 305.6 g. Allowed: 292/316 g.	16.01.19
ProTek RC	ProTek RC # PTK-5100-19		ProTek LiPo 2S 7.6v. 27.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 156.6 g. Allowed: 149/161 g.	16.01.19
ProTek RC	ProTek RC # PTK-5124-19		ProTek LiPo 2S 7.6v. 31.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 155.7 g. Allowed: 149/161 g.	16.01.19
ProTek RC	ProTek RC # PTK-5102-19		ProTek LiPo 2S 7.6v. 37.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 207.2 g. Allowed: 195/211 g.	16.01.19
ProTek RC	ProTek RC # PTK-5114-19		ProTek LiPo 2S 7.6v. 44.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.1 g. Allowed: 207/225 g.	16.01.19
ProTek RC	ProTek RC # PTK-5115-19		ProTek LiPo 2S 7.6v. 46.3 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 268.8 g. Allowed: 259/281 g.	16.01.19
ProTek RC	ProTek RC # PTK-5128-19		ProTek LiPo 2S 7.6v. 53.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 270.5 g. Allowed: 259/281 g.	16.01.19
ProTek RC	ProTek RC # PTK-5127-19		ProTek LiPo 2S 7.6v. 56.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 308.3 g. Allowed: 293/317 g.	16.01.19
ProTek RC	ProTek RC # PTK-5107-19		ProTek LiPo 2S 7.6v. 62.3 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 334.1 g. Allowed: 317/343 g.	16.01.19
Tianco	ORCA Infinite X # LP18IN2S45S		Tianco LiPo 2S 7.4v. 33.3 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 187.6 g. Allowed: 182/198 g.	16.01.19

Tianco	ORCA Infinite X # LP18IN2S54S		Tianco LiPo 2S 7.4v. 40.0 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 223.3 g. Allowed: 215/233 g.	16.01.19
Tianco	ORCA Infinite X # LP18IN2S54T		Tianco LiPo 2S 7.4v. 40.0 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 256.3 g. Allowed: 248/268 g.	16.01.19
Tianco	ORCA Infinite X # LP18IN2S63T		Tianco LiPo 2S 7.4v. 46.6 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 289.6 g. Allowed: 277/301 g.	16.01.19
Neidhart SA	Ultimate # UR4443		Neidhart SA LiPo 2S 7.6v. 30.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 145.3 g. Allowed: 135/147 g.	16.01.19
Neidhart SA	Ultimate # UR4442		Neidhart SA LiPo 2S 7.6v. 44.1 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 210.8 g. Allowed: 204/222 g.	16.01.19
Neidhart SA	Ultimate # UR4425		Neidhart SA LiPo 2S 7.6v. 64.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 284.1 g. Allowed: 280/304 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 5630046		3-Circles LiPo 2S 7.4v. 22.2 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 149.9 g. Allowed: 147/159 g.	16.01.19
Xiamen 3-Circles	Sunpadow # S638066		3-Circles LiPo 2S 7.4v. 28.1 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 161.7 g. Allowed: 157/170 g.	16.01.19
Xiamen 3-Circles	Sunpadow # H640043		3-Circles LiPo 2S 7.6v. 30.4 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 157.6 g. Allowed: 154/166 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 7150135		3-Circles LiPo 2S 7.4v. 33.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 208.2 g. Allowed: 204/220 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 5043126		3-Circles LiPo 2S 7.4v. 37.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.5 g. Allowed: 270/292 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 5651039		3-Circles LiPo 2S 7.4v. 37.7 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 222.3 g. Allowed: 218/236 g.	16.01.19
Xiamen 3-Circles	Sunpadow # S653065		3-Circles LiPo 2S 7.4v. 39.2 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 246.2 g. Allowed: 243/263 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 5042125		3-Circles LiPo 2S 7.4v. 41.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 277.2 g. Allowed: 274/296 g.	16.01.19








Xiamen 3-Circles	Sunpadow # 5442125		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 289.1 g. Allowed: 285/309 g.	16.01.19
Xiamen 3-Circles	Sunpadow # 5542125		3-Circles LiPo 2S 7.4v. 48.8 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 318.4 g. Allowed: 314/340 g.	16.01.19
Xiamen 3-Circles	Sunpadow # S684064		3-Circles LiPo 2S 7.4v. 62.2 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 329.6 g. Allowed: 325/353 g.	16.01.19
Italtrading	EZ-Power # EZP4000-2HV		Ital LiPo 2S 7.6v. 30.4 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 153.6 g. Allowed: 149/161 g.	16.01.19
Miniz Racing	Marka # MRK-LI6000HV- LCG		Miniz Racing LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 255.7 g. Allowed: 248/268 g.	16.01.19
Miniz Racing	Marka # MRK- LI8000HV		Miniz Racing LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 299.7 g. Allowed: 296/320 g.	16.01.19
Ruddog Dist.	Ruddog # RP-0167		Ruddog LiPo 2S 7.6v. 41.8 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 214.0 g. Allowed: 204/222 g.	16.01.19
Ruddog Dist.	Ruddog # RP-0165		Ruddog LiPo 2S 7.6v. 45.6 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 296.0 g. Allowed: 286/310 g.	16.01.19
Ruddog Dist.	Ruddog # RP-0166		Ruddog LiPo 2S 7.6v. 60.8 Wh. 100C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 308.1 g. Allowed: 299/323 g.	16.01.19
Shenzhen Grepow	GensAce # B60C60002S2P HC-29-HV		GensAce LiPo 2S 7.6v. 45.6 Wh. 60C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 208.5 g. Allowed: 202/218 g.	16.01.19
Shenzhen Grepow	GensAce # B120C85002S1 P HC-10-HV-RS		GensAce LiPo 2S 7.6v. 64.6 Wh. 120C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 313.4 g. Allowed: 300/326 g.	16.01.19
Vapex Technology	VP Racing # VP98768		Vapex LiPo 2S 7.6v. 41.8 Wh. 110C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 211.2 g. Allowed: 204/222 g.	16.01.19
Vapex Technology	VP Racing # VP98669		Vapex LiPo 2S 7.6v. 45.6 Wh. 80C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 295.6 g. Allowed: 286/310 g.	16.01.19
Vapex Technology	VP Racing # VP98652		Vapex LiPo 2S 7.6v. 60.8 Wh. 70C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 304.4 g. Allowed: 299/323 g.	16.01.19































Associated Electrics	Reedy Zappers SG # 27325		Reedy LiPo 2S 7.6v. 31.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 152.7 g. Allowed: 144/156 g.	18.01.18
Associated Electrics	Reedy Zappers SG # 27323		Reedy LiPo 2S 7.6v. 45.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.7 g. Allowed: 206/224 g.	18.01.18
Associated Electrics	Reedy Zappers SG # 27321		Reedy LiPo 2S 7.6v. 46.0 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 269.9 g. Allowed: 259/281 g.	18.01.18
Freemax Technology	Arrowmax # AM 700203		Arrowmax LiPo 2S 7.6v. 45.6 Wh. 110C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 213.2 g. Allowed: 211/229 g.	18.01.18
Freemax Technology	Arrowmax # AM 700801		Arrowmax LiPo 2S 7.6v. 39.5 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 245.3 g. Allowed: 235/255 g.	18.01.18
Freemax Technology	Arrowmax # AM 700802		Arrowmax LiPo 2S 7.6v. 47.1 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 280.7 g. Allowed: 272/294 g.	18.01.18
Intellect Battery	IP # LP2S3600HV3		Intellect LiPo 2S 7.6v. 27.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 151.5 g. Allowed: 144/156 g.	18.01.18
Intellect Battery	IP # BG2S5000HV3		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.7 g. Allowed: 192/208 g.	18.01.18
Intellect Battery	IP # BG2S6000HV3		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.1 g. Allowed: 206/224 g.	18.01.18
Intellect Battery	IP # CC2S5200HV3		Intellect LiPo 2S 7.6v. 40.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 243.5 g. Allowed: 230/250 g.	18.01.18
Intellect Battery	IP # CC2S6000HV3		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 268.9 g. Allowed: 259/281 g.	18.01.18
Intellect Battery	IP # CC2S8400HV3		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 329.1 g. Allowed: 315/341 g.	18.01.18
LRP	LRP P5 LCG # 430267		LRP LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 153.8 g. Allowed: 152/164 g.	18.01.18
LRP	LRP P5 # 430266		LRP LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 184.2 g. Allowed: 177/191 g.	18.01.18















LRP	LRP P5 Stock Spec # 430264		LRP LiPo 2S 7.6v. 35.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 206.0 g. Allowed: 196/212 g.	18.01.18
LRP	LRP P5 Stock Spec. # 430265		LRP LiPo 2S 7.6v. 44.1 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.9 g. Allowed: 207/225 g.	18.01.18
LRP	LRP P5 # 430262		LRP LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 237.5 g. Allowed: 221/239 g.	18.01.18
LRP	LRP P5 # 430263		LRP LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 251.7 g. Allowed: 240/260 g.	18.01.18
LRP	LRP P5 Stock Spec # 430261		LRP LiPo 2S 7.6v. 48.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 277.0 g. Allowed: 263/285 g.	18.01.18
LRP	LRP P5 Stock Spec # 430260		LRP LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 332.4 g. Allowed: 317/343 g.	18.01.18
Modern Creations	T/Silverback Spiral G # G52001202S-96		Modern Creations LiPo 2S 7.4v. 38.5 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.2 g. Allowed: 210/228 g.	18.01.18
Modern Creations	T/Silverback Spiral G # G62001202SIN C		Modern Creations LiPo 2S 7.4v. 45.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 283.8 g. Allowed: 275/297 g.	18.01.18
Modern Creations	T/Silverback Spiral III # 64001202SINC		Modern Creations LiPo 2S 7.4v. 47.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 267.1 g. Allowed: 257/279 g.	18.01.18
Modern Creations	T/Silverback Siren HV # HV8000 1002SINA		Modern Creations LiPo 2S 7.6v. 60.8 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 311.1 g. Allowed: 299/323 g.	18.01.18
Neidhart SA	Orion Ultimate # ORI 14511		Orion LiPo 2S 7.4v. 23.7 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 126.6 g. Allowed: 122/132 g.	18.01.18
Neidhart SA	Orion Ultimate HV # ORI 14501		Orion LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 128.7 g. Allowed: 124/134 g.	18.01.18
Neidhart SA	Orion Ultimate # ORI 14512		Orion LiPo 2S 7.4v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 140.5 g. Allowed: 136/148 g.	18.01.18
Neidhart SA	Orion Ultimate HV # ORI 14502		Orion LiPo 2S 7.6v. 30.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 143.4 g. Allowed: 138/150 g.	18.01.18

Neidhart SA	Orion Ultimate # ORI 14513		Orion LiPo 2S 7.4v. 40.7 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 211.7 g. Allowed: 205/223 g.	18.01.18
Neidhart SA	Orion Ultimate HV # ORI 14503		Orion LiPo 2S 7.6v. 44.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.2 g. Allowed: 208/226 g.	18.01.18
Neidhart SA	Orion Ultimate # ORI 14514		Orion LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 264.6 g. Allowed: 253/275 g.	18.01.18
Neidhart SA	Orion Ultimate # ORI 14515		Orion LiPo 2S 7.4v. 50.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes, 4 off.	Sample complies with EFRA dimensions. Weights:- Sample: 299.4 g. Allowed: 285/309 g.	18.01.18
Neidhart SA	Orion Ultimate HV # ORI 14504		Orion LiPo 2S 7.6v. 53.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 285.6 g. Allowed: 273/295 g.	18.01.18
Neidhart SA	Orion Ultimate HV # ORI 14505		Orion LiPo 2S 7.6v. 62.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes, 4 off.	Sample complies with EFRA dimensions. Weights:- Sample: 320.7 g. Allowed: 309/335 g.	18.01.18
Nosram	Nosram P5 # 999550		Nosram LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 184.6 g. Allowed: 177/191 g.	18.01.18
Nosram	Nosram P5 Stock Spec # 999549		Nosram LiPo 2S 7.6v. 44.1 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.7 g. Allowed: 207/225 g.	18.01.18
Nosram	Nosram P5 LCG # 999548		Nosram LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 233.7 g. Allowed: 221/239 g.	18.01.18
Nosram	Nosram P5 Stock Spec # 999547		Nosram LiPo 2S 7.6v. 48.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.5 g. Allowed: 263/285 g.	18.01.18
Nosram	Nosram P5 Stock Spec # 999546		Nosram LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 332.2 g. Allowed: 317/343 g.	18.01.18
RC Concept	Omega # 50C5135000T		RC Concept LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 142.2 g. Allowed: 134/146 g.	18.01.18
RC Concept	Omega # 50C514800000		RC Concept LiPo 2S 7.6v. 36.5 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.5 g. Allowed: 197/213 g.	18.01.18
RC Concept	Omega # 50C5164100T		RC Concept LiPo 2S 7.6v. 48.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 307.0 g. Allowed: 288/312 g.	18.01.18

RC Concept	Omega # 50C51800000		RC Concept LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 302.9 g. Allowed: 288/312 g.	18.01.18
Shenzhen Grepow	GensAce # B100C50002S2 P HC-59-HV-RS		GensAce LiPo 2S 7.6v. 38.0 Wh. 100C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 211.3 g. Allowed: 202/218 g.	18.01.18
Shenzhen Grepow	GensAce # B100C55002S2 P HC-29-HV-RS		GensAce LiPo 2S 7.6v. 41.8 Wh. 100C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 209.6 g. Allowed: 202/218 g.	18.01.18
Shenzhen Grepow	GensAce # B100C60002S1 P HC-49-HV-LCG		GensAce LiPo 2S 7.6v. 45.6 Wh. 100C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 265.0 g. Allowed: 254/276 g.	18.01.18
Shenzhen Grepow	GensAce # B100C75002S1 P HC-47-HV-RS		GensAce LiPo 2S 7.6v. 57.0 Wh. 100C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 312.3 g. Allowed: 298/322 g.	18.01.18
Team Corally	Corally Voltax LCG # 49500		Corally LiPo 2S 7.4v. 31.1 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 181.5 g. Allowed: 175/189 g.	18.01.18
Team Corally	Corally Voltax LCG HV # C-49600		Corally LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 175.6 g. Allowed: 170/184 g.	18.01.18
Team Corally	Corally Voltax # 49505		Corally LiPo 2S 7.4v. 37.0 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 206.1 g. Allowed: 198/214 g.	18.01.18
Team Corally	Corally Voltax HV # C-49605		Corally LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 197.5 g. Allowed: 192/208 g.	18.01.18
Team Corally	Corally Voltax HV # 49606		Corally LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 215.0 g. Allowed: 206/224 g.	18.01.18
Team Corally	Corally Voltax LCG # 49510		Corally LiPo 2S 7.4v. 45.9 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 278.7 g. Allowed: 268/290 g.	18.01.18
Team Corally	Corally Voltax LCG HV # C-49610		Corally LiPo 2S 7.6v. 48.6 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 270.4 g. Allowed: 262/284 g.	18.01.18
Team Corally	Corally Voltax # 49520		Corally LiPo 2S 7.4v. 53.3 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 297.1 g. Allowed: 286/310 g.	18.01.18
Team Corally	Corally Voltax # 49523		Corally LiPo 2S 7.4v. 59.2 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 319.2 g. Allowed: 307/333 g.	18.01.18

Team Corally	Corally Voltax HV # C-49623		Corally LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 310.2 g. Allowed: 300/325 g.	18.01.18
Tianco	ORCA Gen. 4 # OBH454SH		Tianco LiPo 2S 7.6v. 41.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.9 g. Allowed: 192/208 g.	18.01.18
Tianco	ORCA Gen. 4 # OBH455LV		Tianco LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 242.5 g. Allowed: 230/250 g.	18.01.18
Tianco	ORCA Gen. 4 # OBH463H4		Tianco LiPo 2S 7.6v. 47.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 259.4 g. Allowed: 259/281 g.	18.01.18
Tianco	ORCA Gen. 4 # OBH485V4		Tianco LiPo 2S 7.6v. 64.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 331.5 g. Allowed: 315/341 g.	18.01.18
Xiamen 3-Circles	Sunpadow # 7150135		3-Circles LiPo 2S 7.4v. 33.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 222.8 g. Allowed: 212/230 g.	18.01.18
Xiamen 3-Circles	Sunpadow # 554383		3-Circles LiPo 2S 7.4v. 37.7 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.2 g. Allowed: 212/230 g.	18.01.18
Xiamen 3-Circles	Sunpadow # 554385		3-Circles LiPo 2S 7.6v. 45.6 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 209.5 g. Allowed: 202/218 g.	18.01.18
Xiamen 3-Circles	Sunpadow # 5656040		3-Circles LiPo 2S 7.4v. 41.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 271.1 g. Allowed: 261/283 g.	18.01.18
Xiamen 3-Circles	Sunpadow # 5660041		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 287.0 g. Allowed: 277/300 g.	18.01.18
Xiamen 3-Circles	Sunpadow # H663026		3-Circles LiPo 2S 7.6v. 47.9 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 281.2 g. Allowed: 269/291 g.	18.01.18
Xiamen 3-Circles	Sunpadow # H684027		3-Circles LiPo 2S 7.6v. 63.8 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 309.6 g. Allowed: 297/321 g.	18.01.18
Italtrading	EZ-Power # EZP8200/2		Ital LiPo 2S 7.6v. 62.3 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 326.8 g. Allowed: 315/341 g.	18.01.18
Robitronics	Rock Amp # RK5800A2S		Robitronics LiPo 2S 7.6v. 44.0 Wh. 30C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 264.5 g. Allowed: 254/276 g.	18.01.18

Robitronics	Rock Amp # RK6600A2S		Robitronics LiPo 2S 7.6v. 50.1 Wh. 30C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 306.3 g. Allowed: 294/318 g.	18.01.18
Robitronics	Rock Amp # RK7700A2S		Robitronics LiPo 2S 7.6v. 58.5 Wh. 15C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 315.3 g. Allowed: 302/328 g.	18.01.18
Associated Electrics	Reedy Zappers # 27310		Reedy LiPo 2S 7.6v. 28.0 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 151.3 g. Allowed: 149/161 g.	05.01.17
Associated Electrics	Reedy Zappers # 27307		Reedy LiPo 2S 7.6v. 44.0 Wh. 70C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.9 g. Allowed: 215/233 g.	05.01.17
Associated Electrics	Reedy Zappers # 27309		Reedy LiPo 2S 7.6v. 46.0 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 276.4 g. Allowed: 269/291 g.	05.01.17
Freemax Metal Products	Arrowmax # AM 700705		Arrowmax LiPo 2S 7.4v. 38.5 Wh. 130C Max charge rate: 1.2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 274.3 g. Allowed: 264/286 g.	05.01.17
Freemax Metal Products	Arrowmax # AM 700112		Arrowmax LiPo 2S 7.6v. 59.3 Wh. 110C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 317.8 g. Allowed: 303/329 g.	05.01.17
Intellect Battery	IP # LP2S3600HV2		Intellect LiPo 2S 7.6v. 27.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 150.6 g. Allowed: 142/154 g.	05.01.17
Intellect Battery	IP # BG2S5000HV2		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 205.4 g. Allowed: 197/213 g.	05.01.17
Intellect Battery	IP # BG2S6000HV2		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.9 g. Allowed: 216/234 g.	05.01.17
Intellect Battery	IP # CC2S6000HV2		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 275.0 g. Allowed: 259/281 g.	05.01.17
Intellect Battery	IP # CC2S8400HV2		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 332.1 g. Allowed: 317/343 g.	05.01.17
LRP	LRP # 430258		LRP LiPo 2S 7.6v. 22.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 135.1 g. Allowed: 127/137 g.	05.01.17
LRP	LRP # 430257		LRP LiPo 2S 7.6v. 26.6Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 152.2 g. Allowed: 146/158 g.	05.01.17

LRP	LRP # 430256		LRP LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 189.4 g. Allowed: 181/196 g.	05.01.17
LRP	LRP Stock Spec. # 430254		LRP LiPo 2S 7.6v. 35.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 207.3 g. Allowed: 196/212 g.	05.01.17
LRP	LRP Stock Spec. # 430255		LRP LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 223.7 g. Allowed: 213/231 g.	05.01.17
LRP	LRP # 430252		LRP LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 230.8 g. Allowed: 221/239 g.	05.01.17
LRP	LRP Stock Spec. # 430251		LRP LiPo 2S 7.6v. 48.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 274.8 g. Allowed: 261/283 g.	05.01.17
LRP	LRP Stock Spec. # 430250		LRP LiPo 2S 7.6v. 60.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 335.3 g. Allowed: 321/347 g.	05.01.17
Modern Creations	Team Silverback Spiral G # G52001002SIN C		Modern Creations LiPo 2S 7.4v. 38.5 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 279.1 g. Allowed: 265/287 g.	05.01.17
Modern Creations	Team Silverback Siren HV # HV64001002SINC		Modern Creations LiPo 2S 7.6v. 48.6 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 288.7 g. Allowed: 269/291 g.	05.01.17 Typo corrected 03.04.17
Muchmore Racing	Impact # MLI- LCGMP5200		Muchmore LiPo 2S 7.4v. 38.5 Wh. 120C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 275.1 g. Allowed: 263/285 g.	05.01.17
Muchmore Racing	Impact # MLI- LCGHV5200		Muchmore LiPo 2S 7.6v. 39.5 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 244.1 g. Allowed: 235/255 g.	05.01.17
Muchmore Racing	Impact # MLI-LCG6400FD2		Muchmore LiPo 2S 7.4v. 47.4 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 271.0 g. Allowed: 260/282 g.	05.01.17
Nosram	Nosram # 999545		Nosram LiPo 2S 7.6v. 31.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 189.7 g. Allowed: 181/196 g.	05.01.17
Nosram	Nosram # 999544		Nosram LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 231.3 g. Allowed: 221/239 g.	05.01.17
Nosram	Nosram Stock Spec. # 999543		Nosram LiPo 2S 7.6v. 48.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 275.0 g. Allowed: 263/285 g.	05.01.17















ProTek RC	ProTek RC # PTK-5102-17		ProTek LiPo 2S 7.6v. 37.2 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.4 g. Allowed: 197/213 g.	05.01.17
ProTek RC	ProTek RC # PTK-5114-17		ProTek LiPo 2S 7.6v. 46.4 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.0 g. Allowed: 216/234 g.	05.01.17
ProTek RC	ProTek RC # PTK-5115-17		ProTek LiPo 2S 7.6v. 47.9 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 275.7 g. Allowed: 259/281 g.	05.01.17
Shenzhen Grepow	GensAce # B60C32002S1P H/Case 58RS		GensAce LiPo 2S 7.4v. 23.6 Wh. 60C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 151.1 g. Allowed: 144/156 g.	05.01.17
Shenzhen Grepow	GensAce # B60C46002S2P H/Case 29RS		GensAce LiPo 2S 7.4v. 34.1 Wh. 60C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 205.9 g. Allowed: 198/214 g.	05.01.17
Shenzhen Grepow	GensAce # B70C60002S1P H/Case 47RS		GensAce LiPo 2S 7.4v. 44.4 Wh. 70C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 300.7 g. Allowed: 288/312 g.	05.01.17
Shenzhen Grepow	GensAce # B70C72002S1P H/Case 47RS		GensAce LiPo 2S 7.4v. 53.3 Wh. 70C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 301.6 g. Allowed: 288/312 g.	05.01.17
Team Corally	Corally Platinum V+ # 48332		Corally LiPo 2S 7.4v. 25.2 Wh. 100C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 151.9 g. Allowed: 145/157 g.	05.01.17
Team Corally	Corally Coral-X # 48371		Corally LiPo 2S 7.6v. 36.5 Wh. 100C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 196.4 g. Allowed: 188/204 g.	05.01.17
Team Corally	Corally Extreme # 48251		Corally LiPo 2S 7.4v. 40.7 Wh. 90C Max charge rate: 1.1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 201.6 g. Allowed: 193/209 g.	05.01.17
Team Corally	Corally Coral-X # 48372		Corally LiPo 2S 7.6v. 49.4 Wh. 100C Max charge rate: 1.3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 286.1 g. Allowed: 275/297 g.	05.01.17
Team Corally	Corally Coral-X # 48373		Corally LiPo 2S 7.6v. 57.0 Wh. 100C Max charge rate: 1.5C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 299.7 g. Allowed: 289/313 g.	05.01.17
Tianco	ORCA Gen. 3 # OBH350SP		Tianco LiPo 2S 7.6v. 38.0 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.5 g. Allowed: 197/213 g.	05.01.17
Tianco	ORCA Gen. 3 # OBH363R2		Tianco LiPo 2S 7.6v. 47.9 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 272.8 g. Allowed: 259/281 g.	05.01.17

















Tianco	ORCA Gen. 3 # OBH382V3		Tianco LiPo 2S 7.6v. 62.3 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 331.9 g. Allowed: 317/343 g.	05.01.17
Yokomo	Racing Performer # RPB-39E2K		Yokomo LiPo 2S 7.4v. 28.8 Wh. 100C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 159.1 g. Allowed: 154/166 g.	05.01.17
Yokomo	Racing Performer # RPB-50S		Yokomo LiPo 2S 7.4v. 37.0 Wh. 100C Max charge rate: 1C 4 & 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 222.4 g. Allowed: 206/224 g.	05.01.17
Yokomo	Racing Performer # RPB-50LCG		Yokomo LiPo 2S 7.4v. 37.0 Wh. 140C Max charge rate: 1C 4 & 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 274.0 g. Allowed: 262/284 g.	05.01.17
Italtrading	EZ-Power # EZP3500/2		Ital LiPo 2S 7.6v. 26.6 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 147.9 g. Allowed: 142/154 g.	05.01.17
Italtrading	EZ-Power # EZP4900/2		Ital LiPo 2S 7.6v. 37.2 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.0 g. Allowed: 197/213 g.	05.01.17
Italtrading	EZ-Power # EZP6600/2		Ital LiPo 2S 7.6v. 50.2 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 276.1 g. Allowed: 264/286 g.	05.01.17
Miniz Racing	Marka # MRK-LI4700		Miniz LiPo 2S 7.4v. 34.8 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 208.5 g. Allowed: 197/213 g.	05.01.17
Miniz Racing	Marka # MRK-LI6000		Miniz LiPo 2S 7.4v. 44.4 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 291.1 g. Allowed: 283/307 g.	05.01.17
Process Measurement & Analysis	Optipower # OPR40002SB		Optipower LiPo 2S 7.4v. 28.8 Wh. 60C Max charge rate: 2C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.2 g. Allowed: 197/213 g.	05.01.17
R1 Brushless Motor Lab.	R1 # R148002S90C		R1 LiPo 2S 7.4v. 35.5 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.9 g. Allowed: 198/214 g.	05.01.17
R1 Brushless Motor Lab.	R1 # R160002S90C		R1 LiPo 2S 7.4v. 44.4 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 279.2 g. Allowed: 267/289 g.	05.01.17
R1 Brushless Motor Lab.	R1 # R176002S90C		R1 LiPo 2S 7.4v. 56.2 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 335.5 g. Allowed: 324/351 g.	05.01.17
RC ProStyle	RC ProStyle # PS-04280		RC Prostyle LiPo 2S 7.4v. 37.0 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 210.9 g. Allowed: 197/213 g.	05.01.17

RC ProStyle	RC ProStyle # PS-04281		RC Prostyle LiPo 2S 7.4v. 44.4 Wh. 110C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 296.4 g. Allowed: 283/307 g.	05.01.17
RC ProStyle	RC ProStyle # PS-04282		RC Prostyle LiPo 2S 7.4v. 55.5 Wh. 120C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 317.1 g. Allowed: 301/326 g.	05.01.17
Ruddog Dist.	Vampire # VR-1030		Vampire LiPo 2S 7.6v. 45.6 Wh. 80C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 307.3 g. Allowed: 295/319 g.	05.01.17
Associated Electrics	Reedy # 316		Reedy LiPo 2S 7.4v. 37.0 Wh. 65C Wt. 264/286 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 265.6 g.	14.01.16
Associated Electrics	Reedy # 322		Reedy LiPo 2S 7.4v. 40.0 Wh. 70C Wt. 208/226 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 215.0 g.	14.01.16
Associated Electrics	Reedy # 319		Reedy LiPo 2S 7.4v. 29.0 Wh. 70C Wt. 158/172 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 160.8 g.	14.01.16
Freemax Metal Products	Arrowmax # AM 700101		Arrowmax LiPo 2S 7.4v. 37.0 Wh. 55C Wt. 246/266 g. 4 mm or 5mm Tubes.	Sample complies with EFRA dimensions. Sample Wt. 254.7 g.	14.01.16 16.01.18
Freemax Metal Products	Arrowmax # AM 700102		Arrowmax LiPo 2S 7.4v. 44.4 Wh. 65C Wt. 283/307 g. 4mm or 5mm Tubes.	Sample complies with EFRA dimensions. Sample Wt. 294.8 g.	14.01.16 16.01.18
Freemax Metal Products	Arrowmax # AM 700104		Arrowmax LiPo 2S 7.4v. 57.7 Wh. 55C Wt. 311/337 g. 4mm or 5mm Tubes.	Sample complies with EFRA dimensions. Sample Wt. 321.5 g.	14.01.16 16.01.18
Freemax Metal Products	Arrowmax # AM 700202		Arrowmax LiPo 2S 7.4v. 37.0 Wh. 55C Wt. 199/215 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 208.4 g.	14.01.16
Freemax Metal Products	Arrowmax # AM 700401		Arrowmax LiPo 2S 7.4v. 20.7 Wh. 55C Wt. 132/143 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 136.5 g.	14.01.16
Intellect Battery	IP # CC2S3500SV1		Intellect LiPo 2S 7.4v. 26.0 Wh. 100C Wt. 139/151 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 142.7 g.	14.01.16
LRP	LRP # 430234		LRP LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 257/279 g. 5mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 267.5 g.	14.01.16
LRP	LRP # 430232		LRP LiPo 2S 7.4v. 55.5 Wh. 110C Wt. 317/343 g. 5mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 329.9 g.	14.01.16















LRP	LRP Stock Spec. # 's 430217 (4mm) 430233 (5mm)		LRP LiPo 2S 7.4v. 55.5 Wh. 110C Wt. 317/343 g. 4 or 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 333.8 g.	14.01.16
LRP	LRP # 430235		LRP LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 242/262 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 254.0 g.	14.01.16
LRP	LRP # 430239		LRP LiPo 2S 7.4v. 29.6 Wh. 110C Wt. 179/193 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 186.6 g.	14.01.16
LRP	LRP # 430236		LRP LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 198/214 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 203.5 g.	14.01.16
LRP	LRP Stock Spec. # 430237		LRP LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 202/218 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 205.1 g.	14.01.16
LRP	LRP # 430238		LRP LiPo 2S 7.4v. 22.2 Wh. 110C Wt. 136/148 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 144.3 g.	14.01.16
LRP	LRP # 430245		LRP LiPo 2S 7.4v. 19.2 Wh. 110C Wt. 129/139 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 131.9 g.	14.01.16
LRP	LRP # 430400		LRP LiPo 2S 7.4v. 35.5 Wh. 45C Wt. w/wire 230/250 g.	Sample complies with EFRA dimensions.  Sample Wt. 240.3 g.	14.01.16
LRP	LRP # 430401		LRP LiPo 2S 7.4v. 37.0 Wh. 45C Wt. w/wire 238/258 g.	Sample complies with EFRA dimensions.  Sample Wt. 247.7 g.	14.01.16
Modern Creations	Team Silverback Spiral R # 64001002SINA		Modern Creations LiPo 2S 7.4v. 47.3 Wh. 100C Wt. 281/305 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 291.9 g.	14.01.16
Modern Creations	Team Silverback Spiral 2 # 6400902SINC		Modern Creations LiPo 2S 7.4v. 47.3 Wh. 90C Wt. 262/284 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 271.1 g.	14.01.16
Modern Creations	Team Silverback Spiral X # 4100902SIN		Modern Creations LiPo 2S 7.4v. 30.3 Wh. 90C Wt. 154/166 g. 4 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 160.6 g.	14.01.16
Neidhart SA	Orion # ORI 14087		Orion LiPo 2S 7.4v. 42.9 Wh. 110C Wt. 254/276 g. 4mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 265.2 g.	14.01.16
Neidhart SA	Orion # ORI 14068		Orion LiPo 2S 7.4v. 33.3 Wh. 100C Wt. 197/213 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 205.7 g.	14.01.16

Neidhart SA	Orion # ORI 14083		Orion LiPo 2S 7.4v. 37.0 Wh. 110C Wt. 204/221 g. 4mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 217.8 g.	14.01.16
Neidhart SA	Orion # ORI 14081		Orion LiPo 2S 7.4v. 23.7 Wh. 110C Wt. 125/135 g. 4mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 131.5 g.	14.01.16
Neidhart SA	Orion # ORI 14082		Orion LiPo 2S 7.4v. 28.1 Wh. 110C Wt. 146/158 g. 4mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 147.4 g.	14.01.16
Nosram	Nosram X-treme Race # 999527		Nosram LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 257/279 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 266.7 g.	14.01.16
Nosram	Nosram X-treme Race # 999525		Nosram LiPo 2S 7.4v. 55.5 Wh. 110C Wt. 317/343 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 333.9 g.	14.01.16
Nosram	Nosram Stock Spec. # 's 999524 (4mm) 999526 (5mm)		Nosram LiPo 2S 7.4v. 55.5 Wh. 110C Wt. 317/343 g. 4 or 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 331.1 g.	14.01.16
Nosram	Nosram X-treme Race # 999528		Nosram LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 242/262 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 256.4 g.	14.01.16
Nosram	Nosram X-treme Race # 999532		Nosram LiPo 2S 7.4v. 29.6 Wh. 110C Wt. 179/193 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 187.5 g.	14.01.16
Nosram	Nosram X-treme Race # 999529		Nosram LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 198/214 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 206.2 g.	14.01.16
Nosram	Nosram X-treme Race Stock Spec. # 999530		Nosram LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 202/218 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 206.1 g.	14.01.16
Nosram	Nosram X-treme Race # 999531		Nosram LiPo 2S 7.4v. 22.2 Wh. 110C Wt. 136/148 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 145.3 g.	14.01.16
Nosram	Nosram X-treme Race # 999538		Nosram LiPo 2S 7.4v. 19.2 Wh. 110C Wt. 129/139 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 132.9 g.	14.01.16
RC Concept	Omega # 50C5180100T		RC Concept LiPo 2S 7.4v. 59.2 Wh. 100C Wt. 303/329 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 310.5 g.	14.01.16
RC Concept	Omega # 50C5145000T		RC Concept LiPo 2S 7.4v. 33.3 Wh. 100C Wt. 194/210 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 202.2 g.	14.01.16















RC Concept	Omega # 50C5133400T		RC Concept LiPo 2S 7.4v. 24.4 Wh. 100C Wt. w/wire 144/156 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 150.1 g.	14.01.16
Revell GmbH	TrakPower # TKPC0370		TrakPower LiPo 2S 7.4v. 30.0 Wh. 50C Wt. 226/244 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 237.5 g.	14.01.16
Revell GmbH	TrakPower # TKPC0716		TrakPower LiPo 2S 7.4v. 40.0 Wh. 100C Wt. 278/302 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 281.1 g.	14.01.16
Revell GmbH	TrakPower # TKPC0375		TrakPower LiPo 2S 7.4v. 40.0 Wh. 50C Wt. 254/276 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 263.8 g.	14.01.16
Revell GmbH	TrakPower # TKPC0721		TrakPower LiPo 2S 7.4v. 47.0 Wh. 100C Wt. 312/338 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 330.6 g.	14.01.16
Revell GmbH	TrakPower # TKPC0365		TrakPower LiPo 2S 7.4v. 30.0 Wh. 50C Wt. 192/208 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 202.3 g.	14.01.16
Revell GmbH	TrakPower # TKPC0710		TrakPower LiPo 2S 7.4v. 31.0 Wh. 100C Wt. 192/208 g. 5 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 202.1 g.	14.01.16
Revell GmbH	TrakPower # TKPC0707		TrakPower LiPo 2S 7.4v. 22.0 Wh. 100C Wt. 140/152 g. 4 mm. Tubes.	Sample complies with EFRA dimensions.  Sample Wt. 143.9 g.	14.01.16
Shenzhen Grepow	GensAce # B50C50002S1P H/Case 47		GensAce LiPo 2S 7.4v. 37.0 Wh. 50C Wt. 286/310 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 286.5 g.	14.01.16
Shenzhen Grepow	GensAce # B65C53002S1P H/Case 47		GensAce LiPo 2S 7.4v. 39.2 Wh. 65C Wt. 294/318 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 299.9 g.	14.01.16
Shenzhen Grepow	GensAce # B70C60002S1P H/Case 47		GensAce LiPo 2S 7.4v. 44.4 Wh. 70C Wt. 307/333 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 309.4 g.	14.01.16
Shenzhen Grepow	GensAce # B50C65002S1P H/Case 47		GensAce LiPo 2S 7.4v. 48.1 Wh. 50C Wt. 303/329 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 308.4 g.	14.01.16
Shenzhen Grepow	GensAce # B60C42002S2P H/Case 29		GensAce LiPo 2S 7.4v. 31.1 Wh. 60C Wt. 206/224 g. 4 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 212.9 g.	14.01.16
Shenzhen Grepow	GensAce # B60C46002S2P H/Case 29		GensAce LiPo 2S 7.4v. 34.0 Wh. 60C Wt. 197/213 g. 4 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 201.7 g.	14.01.16



Shenzhen Grepow	GensAce # B50C50002S2P H/Case 29A		GensAce LiPo 2S 7.4v. 37.0 Wh. 50C Wt. 202/218 g. 4 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 211.0 g.	14.01.16
Shenzhen Grepow	GensAce # B60C32002S1P H/Case 58		GensAce LiPo 2S 7.4v. 23.7 Wh. 60C Wt. 144/156 g. 4 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 146.9 g.	14.01.16
Vapex Technology	VP Racing # VP96412		Vapex LiPo 2S 7.4v. 45.0 Wh. 80C Wt. 289/313 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 301.8 g.	14.01.16
Vapex Technology	VP Racing # VP96429		Vapex LiPo 2S 7.4v. 58.0 Wh. 70C Wt. 296/320 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 307.4 g.	14.01.16
Vapex Technology	VP Racing # VP96436		Vapex LiPo 2S 7.4v. 39.5 Wh. 70C Wt. 200/216 g. 4 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 209.7 g.	14.01.16
Yokomo	Racing Performer # RPB-60L		Yokomo LiPo 2S 7.4v. 44.4 Wh. 100C Wt. 298/322 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 311.0 g.	14.01.16
Yokomo	Racing Performer # RPB-50S		Yokomo LiPo 2S 7.4v. 37.0 Wh. 100C Wt. 206/224 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 215.5 g.	14.01.16
Yokomo	Racing Performer # RPB-39E2K		Yokomo LiPo 2S 7.4v. 28.8 Wh. 100C Wt. 154/166 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 159.7 g.	14.01.16
French ONPower	ONPower # 75074141		ONPower LiPo 2S 7.4v. 55.5 Wh. 75C Wt. 307/333 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 318.5 g.	14.01.16
French ONPower	ONPower # 46074142		ONPower LiPo 2S 7.4v. 34.0 Wh. 90C Wt. 204/220 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 209.5 g.	14.01.16
Italtrading	EZ-Power # EZP4600/2		Ital LiPo 2S 7.4v. 34.0 Wh. 70C Wt. 202/218 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 209.3 g.	14.01.16
MaxTime	MTB # MTB213		Maxtime LiPo 2S 7.4v. 34.0 Wh. 100C Wt. 207/224 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 216.4 g.	14.01.16
Muchmore Racing	Impact # MLI-MP6200FD2		Muchmore LiPo 2S 7.4v. 45.9 Wh. 110C Wt. 298/322 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 311.3 g.	14.01.16
Muchmore Racing	Impact # MLI-ST5000FD2		Muchmore LiPo 2S 7.4v. 37.0 Wh. 110C Wt. 206/224 g. 4 mm. Tubes.	Sample complies with EFRA dimensions. Sample Wt. 214.4 g.	14.01.16

ProTek RC	ProTek RC # PTKLPH4300 2S100S		ProTek LiPo 2S 7.4v. 31.8 Wh. 100C Wt. 202/218 g. 4 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 205.7 g.	14.01.16
Tianco	ORCA Infinite # OBHV63G2		Tianco LiPo 2S 7.4v. 46.6 Wh. 100C Wt. 271/293 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 281.1 g.	14.01.16
Intellect Battery	IP # CC2S6000SV1		Intellect LiPo 2S 7.4v. 44.0 Wh. 100C Wt. 271/293 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 283.7 g.	08.01.15
Intellect Battery	IP # CC2S7800SV1		Intellect LiPo 2S 7.4v. 58.0 Wh. 100C Wt. 312/338 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 323.8 g.	08.01.15
Intellect Battery	IP # BG2S5000SV1		Intellect LiPo 2S 7.4v. 37.0 Wh. 100C Wt. 202/218 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 211.7 g.	08.01.15
LRP	LRP # 430221		LRP LiPo 2S 7.4v. 40.7 Wh. 110C Wt. 275/297 g.	Sample complies with EFRA dimensions.  Sample Wt. 288.3 g.	08.01.15
LRP	LRP # 430223		LRP LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 261/283 g.	Sample complies with EFRA dimensions.  Sample Wt. 275.6 g.	08.01.15
LRP	LRP # 430222		LRP LiPo 2S 7.4v. 42.9 Wh. 110C Wt. 276/300 g.	Sample complies with EFRA dimensions.  Sample Wt. 288.6 g.	08.01.15
LRP	LRP # 430220		LRP LiPo 2S 7.4v. 51.8 Wh. 110C Wt. 313/339 g.	Sample complies with EFRA dimensions.  Sample Wt. 328.3 g.	08.01.15
LRP	LRP # 430228		LRP LiPo 2S 7.4v. 31.8 Wh. 110C Wt. 204/220 g.	Sample complies with EFRA dimensions.  Sample Wt. 211.2 g.	08.01.15
LRP	LRP # 430227		LRP LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 204/220 g.	Sample complies with EFRA dimensions.  Sample Wt. 210.9 g.	08.01.15
LRP	LRP # 430229		LRP LiPo 2S 7.4v. 21.5 Wh. 110C Wt. 136/148 g.	Sample complies with EFRA dimensions.  Sample Wt. 142.5 g.	08.01.15
LRP	LRP # 430218		LRP LiPo 2S 7.4v. 19.2 Wh. 110C Wt. 129/139 g.	Sample complies with EFRA dimensions.  Sample Wt. 134.0 g.	08.01.15
Modern Creations	Team Silverback SpiralX # 7800902SINA		Modern Creations LiPo 2S 7.4v. 57.7 Wh. 90C Wt. 300/326 g. 5 mm. Tubes	Sample complies with EFRA dimensions.  Sample Wt. 313.5 g.	08.01.15

Modern Creations	Team Silverback SpiralX # 5200902SIN-96		Modern Creations LiPo 2S 7.4v. 38.5 Wh. 90C Wt. 211/229 g.	Sample complies with EFRA dimensions. Sample Wt. 220.4 g.	08.01.15
Muchmore Racing	Impact # MLI-IH6000FD2		Muchmore LiPo 2S 7.4v. 44.4 Wh. 90C Wt. 272/294 g.	Sample complies with EFRA dimensions. Sample Wt. 280.1 g.	08.01.15
Muchmore Racing	Impact # MLI-IH7200FD2		Muchmore LiPo 2S 7.4v. 53.3 Wh. 100C Wt. 307/333 g.	Sample complies with EFRA dimensions. Sample Wt. 325.9 g.	08.01.15
Muchmore Racing	Impact # MLI-ST4500FD2		Muchmore LiPo 2S 7.4v. 33.3 Wh. 90C Wt. 197/213 g.	Sample complies with EFRA dimensions. Sample Wt. 199.8 g.	08.01.15
Nosram	Nosram X-treme Race # 999515		Nosram LiPo 2S 7.4v. 40.7 Wh. 110C Wt. 275/297 g.	Sample complies with EFRA dimensions. Sample Wt. 285.3 g.	08.01.15
Nosram	Nosram X-treme Race # 999517		Nosram LiPo 2S 7.4v. 41.4 Wh. 110C Wt. 261/283 g.	Sample complies with EFRA dimensions. Sample Wt. 275.1 g.	08.01.15
Nosram	Nosram X-treme Race # 999516		Nosram LiPo 2S 7.4v. 42.9 Wh. 110C Wt. 276/300 g.	Sample complies with EFRA dimensions. Sample Wt. 291.0 g.	08.01.15
Nosram	Nosram X-treme Race # 999514		Nosram LiPo 2S 7.4v. 51.8 Wh. 110C Wt. 313/339 g.	Sample complies with EFRA dimensions. Sample Wt. 326.3 g.	08.01.15
Nosram	Nosram X-treme Race # 999522		Nosram LiPo 2S 7.4v. 31.8 Wh. 110C Wt. 204/220 g.	Sample complies with EFRA dimensions. Sample Wt. 215.8 g.	08.01.15
Nosram	Nosram X-treme Race # 999521		Nosram LiPo 2S 7.4v. 33.3 Wh. 110C Wt. 204/220 g.	Sample complies with EFRA dimensions. Sample Wt. 212.7 g.	08.01.15
Nosram	Nosram X-treme Race # 999523		Nosram LiPo 2S 7.4v. 21.5 Wh. 110C Wt. 136/148 g.	Sample complies with EFRA dimensions. Sample Wt. 142.7 g.	08.01.15
Nosram	Nosram X-treme Race # 999512		Nosram LiPo 2S 7.4v. 19.2 Wh. 110C Wt. 129/139 g.	Sample complies with EFRA dimensions. Sample Wt. 134.9 g.	08.01.15
Process Measurement & Analysis	Optipower # OPR55002S50B		Optipower LiPo 2S 7.4v. 40.7 Wh. 50C Wt. 288/312 g.	Sample complies with EFRA dimensions. Sample Wt. 299.6 g.	08.01.15
Process Measurement & Analysis	Optipower # OPR55002S50FL		Optipower LiPo 2S 7.4v. 40.7 Wh. 50C Wt. w/wire 298/322 g.	Sample complies with EFRA dimensions. Sample Wt. 310.3 g.	08.01.15



Process Measurement & Analysis	Optipower # OPR65002S50B		Optipower LiPo 2S 7.4v. 48.1 Wh. 50C Wt. 295/319 g.	Sample complies with EFRA dimensions. Sample Wt. 307.1 g.	08.01.15
Process Measurement & Analysis	Optipower # OPR65002S50FL		Optipower LiPo 2S 7.4v. 48.1 Wh. 50C Wt. w/wire 289/313 g.	Sample complies with EFRA dimensions. Sample Wt. 300.8 g.	08.01.15
Process Measurement & Analysis	Optipower # OPR70002S50B		Optipower LiPo 2S 7.4v. 51.8 Wh. 50C Wt. 300/326 g.	Sample complies with EFRA dimensions. Sample Wt. 313.1 g.	08.01.15
Process Measurement & Analysis	Optipower # OPR70002S50FL		Optipower LiPo 2S 7.4v. 51.8 Wh. 50C Wt. w/wire 302/328 g.	Sample complies with EFRA dimensions. Sample Wt. 314.5 g.	08.01.15
Pro Models Corally	Corally # 48275		Pro Models LiPo 2S 7.4v. 42.9 Wh. 100C Wt. 288/312 g.	Sample complies with EFRA dimensions. Sample Wt. 299.0 g.	08.01.15
Pro Models Corally	Corally # 48276		Prp Models LiPo 2S 7.4v. 50.3 Wh. 100C Wt. 307/333 g.	Sample complies with EFRA dimensions. Sample Wt. 319.6 g.	08.01.15
Pro Models Corally	Corally # 48277		Pro Models LiPo 2S 7.4v. 55.5 Wh. 100C Wt. 298/322 g.	Sample complies with EFRA dimensions. Sample Wt. 309.1 g.	08.01.15
Pro Models Corally	Corally # 48280		Pro Models LiPo 2S 7.4v. 33.3 Wh. 100C Wt. 198/214 g.	Sample complies with EFRA dimensions. Sample Wt. 205.6 g.	08.01.15
Pro Models Corally	Corally # 48262		Pro Models LiPo 2S 7.4v. 35.5 Wh. 90C Wt. 193/209 g.	Sample complies with EFRA dimensions. Sample Wt. 200.7 g.	08.01.15
ProTek RC	ProTek RC # PTK 5104-15		ProTek LiPo 2S 7.4v. 39.2 Wh. 100C Wt. 271/293 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 283.9 g.	08.01.15
ProTek RC	ProTek RC # PTK 5107-15		ProTek LiPo 2S 7.4v. 47.4 Wh. 100C Wt. 312/338 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 324.9 g.	08.01.15
ProTek RC	ProTek RC # PTK 5102-15		ProTek LiPo 2S 7.4v. 31.5 Wh. 100C Wt. 202/218 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 209.3 g.	08.01.15
ProTek RC	ProTek RC # PTK 5100-15		ProTek LiPo 2S 7.4v. 20.7 Wh. 100C Wt. 141/153 g.	Sample complies with EFRA dimensions. Sample Wt. 147.9 g.	08.01.15
Ruddog Dist.	Vampire # VR-1027		Vampire LiPo 2S 7.4v. 47.4 Wh. 100C Wt. 307/333 g.	Sample complies with EFRA dimensions. Sample Wt. 317.9 g.	08.01.15

Ruddog Dist.	Vampire # VR-1026		Vampire LiPo 2S 7.4v. 55.5 Wh. 80C Wt. 317/343 g.	Sample complies with EFRA dimensions. Sample Wt. 327.0 g.	08.01.15
Ruddog Dist.	Vampire # VR-1028		Vampire LiPo 2S 7.4v. 34.0 Wh. 80C Wt. 211/229 g.	Sample complies with EFRA dimensions. Sample Wt. 217.4 g.	08.01.15
Shenzhen Grepow	GensAce # B70C72002S1 P H/Case10		GensAce LiPo 2S 7.4v. 53.3 Wh. 70C Wt. 302/327 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 314.1 g.	08.01.15
Tianco	ORCA Infinite # OBHV62N8		Tianco LiPo 2S 7.4v. 45.9 Wh. 100C Wt. 271/293 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 282.6 g.	08.01.15
Tianco	ORCA Infinite # OBHV75I9		Tianco LiPo 2S 7.4v. 55.5 Wh. 100C Wt. 312/338 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 325.8 g.	08.01.15
Tianco	ORCA Infinite # OBHV48F7		Tianco LiPo 2S 7.4v. 35.5 Wh. 100C Wt. 202/218 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 214.1 g.	08.01.15
Yokomo	Racing Performer # RBP-58R		Yokomo LiPo 2S 7.4v. 42.9 Wh. 100C Wt. 263/285 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 274.0 g.	08.01.15
Yokomo	Racing Performer # RBP-48S		Yokomo LiPo 2S 7.4v. 35.5 Wh. 100C Wt. 202/218 g. 5 mm. Tubes	Sample complies with EFRA dimensions. Sample Wt. 213.0 g.	08.01.15
Yokomo	Racing Performer # RBP-35E2		Yokomo LiPo 2S 7.4v. 25.9 Wh. 100C Wt. 141/153 g.	Sample complies with EFRA dimensions. Sample Wt. 144.9 g.	08.01.15
MaxTime	MTB # MTB315		Maxtime LiPo 2S 7.4v. 48.1 Wh. 100C Wt. 303/329 g.	Sample complies with EFRA dimensions. Sample Wt. 316.1 g.	08.01.15
Associated Electrics	Reedy # 602		Reedy LiPo 2S 7.4v. 31.0 Wh. 65C Wt. 200/216 g.	Approved for 2013. Label design updated for 2015. Specification not changed.	08.01.15
Associated Electrics	Reedy # 313		Reedy LiPo 2S 7.4v. 52.0 Wh. 65C Wt. 305/331 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 315.6 g.	05.01.14
CS- Electronic	CS Professional # C211032		CS LiPo 2S 7.4v. 56.3 Wh. 90C Wt. 321/347 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 328.9 g.	05.01.14
CS- Electronic	CS Professional # C211026		CS LiPo 2S 7.4v. 35.5 Wh. 90C Wt. 209/227 g.	Sample complies with EFRA dimensions. Wt. 215.9 g.	05.01.14

Hacker Motor	Hacker Top Fuel # 77200277		Hacker LiPo 2S 7.4v. 50.3 Wh. 90C Wt. 300/325 g.	Sample complies with EFRA dimensions. Wt. 300.6 g.	05.01.14
Hacker Motor	Hacker Top Fuel # 74500277		Hacker LiPo 2S 7.4v. 31.1 Wh. 90C Wt. 199/215 g.	Sample complies with EFRA dimensions. Wt. 204.7 g.	05.01.14
Hobbico RC	TrakPower # TKPC0616		TrakPower LiPo 2S 7.4v. 42.0 Wh. 90C Wt. 283/306 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 294.8 g.	05.01.14
Hobbico RC	TrakPower # TKPC0621		TrakPower LiPo 2S 7.4v. 54.0 Wh. 90C Wt. 312/338 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 336.0 g.	05.01.14
Hobbico RC	TrakPower # TKPC0610		TrakPower LiPo 2S 7.4v. 34.0 Wh. 90C Wt. 211/229 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 220.2 g.	05.01.14
Hobbico RC	TrakPower # TKPC0607		TrakPower LiPo 2S 7.4v. 24.0 Wh. 90C Wt. 144/156 g.	Sample complies with EFRA dimensions. Wt. 153.2 g.	05.01.14
Intellect Battery	IP # CC2S6000V9		Intellect LiPo 2S 7.4v. 44.0 Wh. 90C Wt. 283/307 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 295.6 g.	05.01.14
Intellect Battery	IP # CC2S7600V9		Intellect LiPo 2S 7.4v. 56.0 Wh. 90C Wt. 321/348 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 336.5 g.	05.01.14
Intellect Battery	IP # BG2S4800V9		Intellect LiPo 2S 7.4v. 36.0 Wh. 90C Wt. 211/229 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 219.8 g.	05.01.14
VTEC LRP	VTEC # 430211		LRP LiPo 2S 7.4v. 44.4 Wh. 55C Wt. 282/306 g.	Sample complies with EFRA dimensions. Wt. 294.3 g.	05.01.14
VTEC LRP	VTEC # 430210		LRP LiPo 2S 7.4v. 55.5 Wh. 55C Wt. 318/345 g.	Sample complies with EFRA dimensions. Wt. 334.2 g.	05.01.14
VTEC LRP	VTEC # 430214		LRP LiPo 2S 7.4v. 34.8 Wh. 55C Wt. 213/231 g.	Sample complies with EFRA dimensions. Wt. 221.8 g.	05.01.14
Modern Creations	Team Silverback Elite # 5300502SINA		Team Silverback LiPo 2S 7.4v. 39.22 Wh. 50C Wt. 245/265 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 254.9 g.	05.01.14
Modern Creations	Team Silverback SpiralX # 6300902SINA		Team Silverback LiPo 2S 7.4v. 46.62 Wh. 90C Wt. 283/307 g. 5mm. Tubes	Sample complies with EFRA dimensions. Wt. 294.2 g.	05.01.14

Modern Creations	Team Silverback Spiral # 7200802SINA		Team Silverback LiPo 2S 7.4v. 53.28 Wh. 80C Wt. 297/322 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 312.0 g.	05.01.14
Muchmore Racing	Muchmore Impact # MLI-IH6000SP		Muchmore LiPo 2S 7.4v. 44.4 Wh. 80C Wt. 278/302 g.	Sample complies with EFRA dimensions.  Wt. 288.5 g.	05.01.14
Muchmore Racing	Muchmore Impact # MLI-ST4600FD		Muchmore LiPo 2S 7.4v. 34.0 Wh. 80C Wt. 211/229 g.	Sample complies with EFRA dimensions.  Wt. 221.9 g.	05.01.14
Neidhart SA	ORION Carbon Pro # ORI 14061		Orion LiPo 2S 7.4v. 42.9 Wh. 100C Wt. 296/320 g.	Sample complies with EFRA dimensions.  Wt. 307.7 g.	05.01.14
Neidhart SA	ORION Carbon Pro # ORI 14062		Orion LiPo 2S 7.4v. 50.3 Wh. 100C Wt. 301/327 g.	Sample complies with EFRA dimensions.  Wt. 312.4 g.	05.01.14
Neidhart SA	ORION Carbon Pro # ORI 14060		Orion LiPo 2S 7.4v. 50.3 Wh. 100C Wt. w/wire 305/331 g.	Sample complies with EFRA dimensions.  Wt. w/wires 316.1 g.	05.01.14
Neidhart SA	ORION Carbon Pro # ORI 14066		Orion LiPo 2S 7.4v. 31.1 Wh. 100C Wt. 198/214 g.	Sample complies with EFRA dimensions.  Wt. 203.4 g.	05.01.14
VTEC Nosram	Nosram X-treme Race # 999508		Nosram LiPo 2S 7.4v. 44.4 Wh. 55C Wt. 282/306 g.	Sample complies with EFRA dimensions.  Wt. 294.3 g.	05.01.14
VTEC Nosram	Nosram X-treme Race # 999507		Nosram LiPo 2S 7.4v. 55.5 Wh. 55C Wt. 318/345 g.	Sample complies with EFRA dimensions.  Wt. 334.2 g.	05.01.14
VTEC Nosram	Nosram X-treme Race # 999511		Nosram LiPo 2S 7.4v. 34.8 Wh. 55C Wt. 213/231 g.	Sample complies with EFRA dimensions.  Wt. 221.8 g.	05.01.14
Pro Models BVBA	Corally # 48257		Corally LiPo 2S 7.4v. 44.4 Wh. 90C Wt. 286/310 g.	Sample complies with EFRA dimensions.  Wt. 299.4 g.	05.01.14
Pro Models BVBA	Corally # 48256		Corally LiPo 2S 7.4v. 51.8 Wh. 90C Wt. 307/333 g.	Sample complies with EFRA dimensions.  Wt. 319.9 g.	05.01.14
Pro Models BVBA	Corally # 48255		Corally LiPo 2S 7.4v. 59.2 Wh. 90C Wt. 312/338 g.	Sample complies with EFRA dimensions.  Wt. 318.6 g.	05.01.14
ProTek RC	ProTek RC # PTK 5104-14		ProTek LiPo 2S 7.4v. 42.9 Wh. 100C Wt. 283/307 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 295.0 g.	05.01.14

ProTek RC	ProTek RC # PTK 5107-14		ProTek LiPo 2S 7.4v. 54.7 Wh. 100C Wt. 321/348 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 336.8 g.	05.01.14
ProTek RC	ProTek RC # PTK 5102-14		ProTek LiPo 2S 7.4v. 34.7 Wh. 100C Wt. 211/229 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 221.5 g.	05.01.14
ProTek RC	ProTek RC # PTK 5100-14		ProTek LiPo 2S 7.4v. 23.6 Wh. 100C Wt. 144/156 g.	Sample complies with EFRA dimensions.  Wt. 153.4 g.	05.01.14
Tianco	ORCA Infinite # OB6290G6		Orca LiPo 2S 7.4v. 45.9 Wh. 90C Wt. 283/307 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 295.7 g.	05.01.14
Tianco	ORCA Infinite # OB7590GT		Orca LiPo 2S 7.4v. 55.5 Wh. 90C Wt. 322/348 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 339.5 g.	05.01.14
Tianco	ORCA Infinite # OB4890P5		Orca LiPo 2S 7.4v. 35.5 Wh. 90C Wt. 211/229 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 221.0 g.	05.01.14
Trinity Revtech Epic	RevTech FormulaX # REV2021-5		Revtech LiPo 2S 7.4v. 52.9 Wh. 100C Wt. 298/322 g. 5mm. Tubes	Sample complies with EFRA dimensions.  Wt. 310.2 g.	05.01.14
Xcite RC	Xcite Energy XXL # 56600103		Xcite LiPo 2S 7.4v. 42.9 Wh. 80C Wt. 283/307 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Wt. 296.0 g.	05.01.14
Xcite RC	Xcite Energy XXL # 56600102		Xcite LiPo 2S 7.4v. 54.8 Wh. 80C Wt. 322/348 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Wt. 337.4 g.	05.01.14
Xcite RC	Xcite Energy XXL # 56600105		Xcite LiPo 2S 7.4v. 34.0 Wh. 80C Wt. 211/229 g. 5mm. Tubes.	Sample complies with EFRA dimensions.  Wt. 221.5 g.	05.01.14
Fullymax	Fullymax # FB6400 80C 7.4 WB		Fullymax LiPo 2S 7.4v. 47.3 Wh. 80C Wt. 307/333 g.	Sample complies with EFRA dimensions.  Wt. 315.4 g.	05.01.14
Fullymax	Fullymax # FB7500 45C 7.4 WB		Fullymax LiPo 2S 7.4v. 55.5 Wh. 45C Wt. 314/340 g.	Sample complies with EFRA dimensions.  Wt. 322.1 g.	05.01.14
Graupner	GM V-MAXX # 99031		GM LiPo 2S 7.4v. 56.2 Wh. 100C Wt. 322/348 g.	Sample complies with EFRA dimensions.  Wt. 328.6 g.	05.01.14
Moore Speed	Moore-Speed # MS-B7408		M/Speed LiPo 2S 7.4v. 45.9 Wh. 80C Wt. 295/319 g.	Sample complies with EFRA dimensions.  Wt. 310.4 g.	05.01.14

nVision	nVision # NVO 1120		nVision LiPo 2S 7.4v. 42.9 Wh. 100C Wt. 302/327 g.	Sample complies with EFRA dimensions. Wt. 313.2 g.	05.01.14
nVision	nVision # NVO 1118		nVision LiPo 2S 7.4v. 42.9 Wh. 100C Wt. w/wire 305/331 g.	Sample complies with EFRA dimensions. Wt. w/wires 317.6 g.	05.01.14
nVision	nVision # NVO 1121		nVision LiPo 2S 7.4v. 50.3 Wh. 100C Wt. 308/334 g.	Sample complies with EFRA dimensions. Wt. 319.1 g.	05.01.14
nVision	nVision # NVO 1119		nVision LiPo 2S 7.4v. 50.3 Wh. 100C Wt. w/wire 311/337 g.	Sample complies with EFRA dimensions. Wt. w/wires 322.0 g.	05.01.14
nVision	nVision # NVO 1125		nVision LiPo 2S 7.4v. 31.1 Wh. 100C Wt. 197/213 g.	Sample complies with EFRA dimensions. Wt. 202.9 g.	05.01.14
RC Industries Int.	Pro Amps # PA6060002S		Pro Amps LiPo 2S 7.4v. 44.4 Wh. 60C Wt. 292/316 g.	Sample complies with EFRA dimensions. Wt. 303.2 g.	05.01.14
RC Industries Int.	Pro Amps # PA6042002S2P		Pro Amps LiPo 2S 7.4v. 31.1 Wh. 60C Wt. 185/201 g.	Sample complies with EFRA dimensions. Wt. 194.8 g.	05.01.14
Shanghai Dualsky	Track & Field # 31085		Dualsky LiPo 2S 7.4v. 51.8 Wh. 80C Wt. 301/327 g. 5mm. Tubes.	Sample complies with EFRA dimensions. Wt. 326.4 g.	05.01.14
Shanghai Dualsky	Track & Field # 31097		Dualsky LiPo 2S 7.4v. 34.0 Wh. 75C Wt. 202/218 g.	Sample complies with EFRA dimensions. Wt. 207.7 g.	05.01.14
Shenzhen Acepow Electronics	Gens ace # B50C50002S1 PH/Case10		Acepow LiPo 2S 7.4v. 37.0 Wh. 50C Wt. 291/316 g.	Sample complies with EFRA dimensions. Wt. 292.3 g.	05.01.14
Shenzhen Acepow Electronics	Gens ace # B65C53002S1 PH/Case10		Acepow LiPo 2S 7.4v. 39.2 Wh. 65C Wt. 301/326 g.	Sample complies with EFRA dimensions. Wt. 301.9 g.	05.01.14
Shenzhen Acepow Electronics	Gens ace # B45C58002S2 PH/Case10		Acepow LiPo 2S 7.4v. 42.9 Wh. 45C Wt. 304/329 g.	Sample complies with EFRA dimensions. Wt. 304.7 g.	05.01.14