

EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.

BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Lithium based (LiPo) batteries detailed below, are approved for various EFRA Electric Classes. Section Rules will detail the type applicable. Availability dates for new EFRA compliant Packs are not known at the date of publishing this list. Manufacturers have confirmed March 2026 latest.

EFRA rules limit battery energy capacity to comply with Airline Requirements (currently 100Wh.), based on Manufacturers data below.

Batteries approved from 2011 onwards must comply with the weight range specified. Batteries factory sealed (glue, weld etc.).




Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed.















Manufacturers advise that charge rate be restricted to 1C for optimum lifespan, but should not be more than stated below (for 2017 on).

Batteries MUST be charged using a 2S LiPo compatible charger. LiPo 'Sack' must be used when charging or discharging prior to race.

It is strictly NOT ALLOWED, to charge 2S LiPo Batteries to give an output voltage exceeding 8.40v.













EFRA: MAXIMUM dimensions for Battery Case size:- Length = 139.0 mm. Width = 47.0 mm. Height = 25.1 mm. (No + tolerance allowed)








Submitted by:	Label Details Part #	Illustration only	Manufacturer Supplied Data.	EFRA measured Specification,	Approval Date
BATTERIES BELOW ARE APPROVED BY EFRA FOR 2026, BUT NOT ALLOWED AT EFRA 2026 EVENTS UNTIL 01.04.26.					
Absima	Absima V2 # 4150028		Absima LiPo 2S 7.6v. 33.44 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 153/165 g.	01.01.26
Absima	Absima V2 # 4150029		Absima LiPo 2S 7.6v. 38.0 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 163/177 g.	01.01.26
Absima	Absima V2 # 4150030		Absima LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 213/231 g.	01.01.26
Absima	Absima V2 # 4150032		Absima LiPo 2S 7.6v. 53.2 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 235/255 g.	01.01.26
Associated Electrics	Reedy Zappers SG7 # 27618		Reedy LiPo 2S 7.6v. 36.48 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26
Associated Electrics	Reedy Stockstar # 27611		Reedy LiPo 2S 7.4v. 37.0 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 171/185 g.	01.01.26
Associated Electrics	Reedy Zappers SG7 # 27616		Reedy LiPo 2S 7.6v. 47.12 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 223/241 g.	01.01.26
Associated Electrics	Reedy Zappers SG7 # 27617		Reedy LiPo 2S 7.6v. 50.16 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 211/229 g.	01.01.26
Associated Electrics	Reedy Stockstar # 27613		Reedy LiPo 2S 7.4v. 49.58 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 240/260 g.	01.01.26
Intellect Pioneering Battery Technology	IP # BL2S4600MC4		Intellect LiPo 2S 7.6v. 35.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 149/161 g.	01.01.26

Intellect Pioneering Battery Technology	IP # BL2S5000MC4		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26
Intellect Pioneering Battery Technology	IP # BT2S6000MC4		Intellect LiPo 2S 7.6v. 46.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 208/226 g.	01.01.26
Intellect Pioneering Battery Technology	IP # CM2S6200MC4		Intellect LiPo 2S 7.6v. 48.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 223/241 g.	01.01.26
Intellect Pioneering Battery Technology	IP # BT2S6600MC4		Intellect LiPo 2S 7.6v. 51.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 211/229 g.	01.01.26
Intellect Pioneering Battery Technology	IP # CM2S7000MC4		Intellect LiPo 2S 7.6v. 54.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 235/255 g.	01.01.26
Intellect Pioneering Battery Technology	IP # DT2S7400MC4		Intellect LiPo 2S 7.6v. 57.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 250/270 g.	01.01.26
Intellect Pioneering Battery Technology	IP # DT2S7800MC4		Intellect LiPo 2S 7.6v. 60.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 250/270 g.	01.01.26
Intellect Pioneering Battery Technology	IP # CT2S10400MC4		Intellect LiPo 2S 7.6v. 80.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 317/343 g.	01.01.26
Italtrading	EZ ICE Series # EZP4600/2		Ital LiPo 2S 7.6v. 34.96 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 149/161 g.	01.01.26
Italtrading	EZ ICE Series # EZP4900/2		Ital LiPo 2S 7.6v. 37.24 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 168/182 g.	01.01.26
Italtrading	EZ ICE Series # EZP6300/2		Ital LiPo 2S 7.6v. 47.88 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 223/241 g.	01.01.26
Italtrading	EZ ICE Series # EZP6700/2		Ital LiPo 2S 7.6v. 50.92 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 211/229 g.	01.01.26
Italtrading	EZ ICE Series # EZP7200/2		Ital LiPo 2S 7.6v. 54.72 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 235/255 g.	01.01.26
Italtrading	EZ ICE Series # EZP9800/2		Ital LiPo 2S 7.6v. 74.48 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 322/348 g.	01.01.26












LRP	LRP G4.2 LCG # 432274		LRP LiPo 2S 7.6v. 33.4 Wh. 145C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 167/181 g.	01.01.26
LRP	LRP G4.2 LCG # 433273		LRP LiPo 2S 7.6v. 35.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 155/167 g.	01.01.26
LRP	LRP G4.2 LCG # 433288		LRP LiPo 2S 7.6v. 37.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26
LRP	LRP G4.2 LCG # 433286		LRP LiPo 2S 7.6v. 41.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 187/203 g.	01.01.26
LRP	LRP G4.2 LCG # 433272		LRP LiPo 2S 7.6v. 44.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 208/226 g.	01.01.26
LRP	LRP G4.2 LCG # 433277		LRP LiPo 2S 7.6v. 47.9 Wh. 145C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 228/246 g.	01.01.26
LRP	LRP G4.2 LCG # 433282		LRP LiPo 2S 7.6v. 54.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 236/256 g.	01.01.26
LRP	LRP G4.2 LCG # 433271		LRP LiPo 2S 7.6v. 57.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 265/287 g.	01.01.26
LRP	LRP G4.2 Mid size # 433263		LRP LiPo 2S 7.6v. 60.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 256/278 g.	01.01.26
LRP	LRP G4.2 Modified # 433289		LRP LiPo 2S 7.6v. 75.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 322/348 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999863		Nosram LiPo 2S 7.6v. 33.4 Wh. 145C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 167/181 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999853		Nosram LiPo 2S 7.6v. 35.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 155/167 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999861		Nosram LiPo 2S 7.6v. 37.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999860		Nosram LiPo 2S 7.6v. 41.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 187/203 g.	01.01.26

Nosram	Nosram G4.2 LCG # 999864		Nosram LiPo 2S 7.6v. 44.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 208/226 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999846		Nosram LiPo 2S 7.6v. 47.9 Wh. 145C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 228/246 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999858		Nosram LiPo 2S 7.6v. 54.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 236/256 g.	01.01.26
Nosram	Nosram G4.2 LCG # 999857		Nosram LiPo 2S 7.6v. 57.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 265/287 g.	01.01.26
Nosram	Nosram G4.2 Mid size # 999849		Nosram LiPo 2S 7.6v. 60.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 255/277 g.	01.01.26
Nosram	Nosram G4.2 Modified # 999862		Nosram LiPo 2S 7.6v. 75.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 322/348 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5124-26		ProTek LiPo 2S 7.6v. 34.9 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 149/161 g.	01.01.26
ProTek RC	ProTek RC Stockspec # PTK-5147-26		ProTek LiPo 2S 7.4v. 35.5 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 182/198 g.	01.01.26
ProTek RC	ProTek RC Rivkin Ed. # PTK-5143-26		ProTek LiPo 2S 7.6v. 37.2 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5126-25		ProTek LiPo 2S 7.4v. 41.4 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 215/233 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5102-26		ProTek LiPo 2S 7.6v. 45.6 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 208/226 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5146-26		ProTek LiPo 2S 7.6v. 47.8 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 223/241 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5114-26		ProTek LiPo 2S 7.6v. 51.6 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 211/229 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5128-26		ProTek LiPo 2S 7.6v. 53.9 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 235/255 g.	01.01.26




ProTek RC	ProTek RC SG3 # PTK-5138-26		ProTek LiPo 2S 7.6v. 56.2 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 250/270 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5145-26		ProTek LiPo 2S 7.6v. 59.2 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 259/281 g.	01.01.26
ProTek RC	ProTek RC SG3 # PTK-5133-26		ProTek LiPo 2S 7.6v. 76.0 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 317/343 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0852		Ruddog LiPo 2S 7.4v. 33.3 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 170/184 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0853		Ruddog LiPo 2S 7.6v. 35.72 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 158/172 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0854		Ruddog LiPo 2S 7.6v. 38.0 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 170/184 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0857		Ruddog LiPo 2S 7.4v. 37.74 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 209/227 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0855		Ruddog LiPo 2S 7.6v. 41.04 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 187/203 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0858		Ruddog LiPo 2S 7.4v. 46.62 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 236/256 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0856		Ruddog LiPo 2S 7.6v. 48.64 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 217/235 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0859		Ruddog LiPo 2S 7.6v. 53.96 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 230/250 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0861		Ruddog LiPo 2S 7.6v. 58.52 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 252/272 g.	01.01.26
Ruddog Distribution	Ruddog RR2 # RP-0860		Ruddog LiPo 2S 7.6v. 76.0 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 316/342 g.	01.01.26
Schumacher Racing	Aerox Elite V.3 # AX053		Schumacher LiPo 2S 7.4v. 34.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 163/177 g.	01.01.26














Schumacher Racing	Aerox Elite V.3 # AX056		Schumacher LiPo 2S 7.4v. 44.4 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 233/253 g.	01.01.26
Schumacher Racing	Aerox Elite V.3 # AX052		Schumacher LiPo 2S 7.4v. 48.84 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 236/256 g.	01.01.26
Shenzhen Cayote Technology	Cayote # CYE562S145		Cayote LiPo 2S 7.6v. 42.56 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 192/208 g.	01.01.26
Shenzhen Cayote Technology	Cayote # CYE722S145		Cayote LiPo 2S 7.6v. 54.72 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 243/263 g.	01.01.26
Shenzhen Cayote Technology	Cayote # CYE872S145B		Cayote LiPo 2S 7.4v. 64.38 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 308/334 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA4000 2S14NV		GensAce LiPo 2S 7.4v. 29.6 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 163/177 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA4600 2S14NV		GensAce LiPo 2S 7.4v. 34.04 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 180/196 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA5000 2S14NV		GensAce LiPo 2S 7.4v. 37.0 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 203/219 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA5200 2S14D5		GensAce LiPo 2S 7.6v. 39.52 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 191/207 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA6000 2S14NV		GensAce LiPo 2S 7.4v. 44.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 242/262 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA6600 2S14NV		GensAce LiPo 2S 7.4v. 48.84 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 269/291 g.	01.01.26
Shenzhen Grepow	GensAce Redline 2.0 # GEA8100 2S14NV		GensAce LiPo 2S 7.4v. 59.94 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 304/330 g.	01.01.26
Shenzhen Saikette Technology	DXF Golden NGP Plus # D66431262S		DXF LiPo 2S 7.6v. 50.16 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 251/271 g.	01.01.26
Shenzhen Saikette Technology	DXF Golden NGP # D7043962S		DXF LiPo 2S 7.6v. 53.2 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 218/236 g.	01.01.26















Shenzhen Saikette Technology	DXF Golden NGP Plus # NGP7000MID		DXF LiPo 2S 7.6v. 53.2 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 256/278 g.	01.01.26
Shenzhen Saikette Technology	DXF Golden NGP Plus # D10000431262S		DXF LiPo 2S 7.6v. 76.0 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 327/355 g.	01.01.26
Team EAM	EAM # EAM46160-2		EAM LiPo 2S 7.4v. 34.04 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 160/174 g.	01.01.26
Team EAM	EAM # EAM52200-2		EAM LiPo 2S 7.4v. 38.48 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 206/224 g.	01.01.26
Team EAM	EAM # EAM56150-2		EAM LiPo 2S 7.4v. 41.1 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 224/242 g.	01.01.26
Team EAM	EAM # EAM60160-2		EAM LiPo 2S 7.4v. 44.4 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 219/237 g.	01.01.26
Team EAM	EAM # EAM64150-2		EAM LiPo 2S 7.4v. 47.4 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 245/265 g.	01.01.26
Team EAM	EAM # EAM66160-2		EAM LiPo 2S 7.4v. 48.84 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 239/259 g.	01.01.26
Team EAM	EAM # EAM70200-2		EAM LiPo 2S 7.4v. 51.8 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 266/288 g.	01.01.26
Team EAM	EAM # EAM77160-2		EAM LiPo 2S 7.6v. 58.52 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 252/274 g.	01.01.26
Team EAM	EAM # EAM80200-2		EAM LiPo 2S 7.4v. 59.2 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 300/324 g.	01.01.26
Team EAM	EAM # EAM92160-2		EAM LiPo 2S 7.6v. 69.92 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 313/339 g.	01.01.26
Team Exalt	Exalt X Rated # EXA3215		Exalt LiPo 2S 7.4v. 50.32 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 266/288 g.	01.01.26
TPRO Electronics	TPRO # TP73021		TPRO LiPo 2S 7.6v. 36.5 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 166/180 g.	01.01.26

TPRO Electronics	TPRO # TP73022		TPRO LiPo 2S 7.6v. 50.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 211/229 g.	01.01.26
TPRO Electronics	TPRO # TP73023		TPRO LiPo 2S 7.6v. 56.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 250/270 g.	01.01.26
Xiamen 3-Circles	Sunpadow # RBJ0011H		3-Circles LiPo 2S 7.6v. 36.48 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 170/184 g.	01.01.26
Xiamen 3-Circles	Sunpadow # RBJ0010H		3-Circles LiPo 2S 7.6v. 40.28 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 187/203 g.	01.01.26
Xiamen 3-Circles	Sunpadow Platin # JA0001		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 271/293 g.	01.01.26
Xiamen 3-Circles	Sunpadow # RBJ0009H		3-Circles LiPo 2S 7.6v. 48.64 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 222/240 g.	01.01.26
Xiamen 3-Circles	Sunpadow # RBJ0008H		3-Circles LiPo 2S 7.6v. 51.68 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 254/276 g.	01.01.26
Xiamen 3-Circles	Sunpadow # RBJ0007H		3-Circles LiPo 2S 7.6v. 72.96 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 329/357 g.	01.01.26
XTR Racing	XTR # XTR-0304		XTR LiPo 2S 7.6v. 50.16 Wh. 150C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 216/234 g.	01.01.26
XTR Racing	XTR # XTR-0330		XTR LiPo 2S 7.6v. 55.48 Wh. 150C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 244/264 g.	01.01.26
XTR Racing	XTR # XTR-0263		XTR LiPo 2S 7.6v. 72.2 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with maximum dimensions. Weights allowed:- 311/337 g.	01.01.26

BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2025 AND ARE ALLOWED AT 2026 EVENTS.

Absima	Absima # AB4150020		Absima LiPo 2S 7.6v. 31.92 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 157.4 g. Allowed: 151/164 g.	01.01.25
Absima	Absima # AB4150021		Absima LiPo 2S 7.6v. 40.28 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 200.1 g. Allowed: 191/207 g.	01.01.25
Absima	Absima # AB4150022		Absima LiPo 2S 7.6v. 45.60 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 221.7 g. Allowed: 213/230 g.	01.01.25

Absima	Absima # AB4150023		Absima LiPo 2S 7.6v. 49.40 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 267.9 g. Allowed: 257/278 g.	01.01.25
Absima	Absima # AB4150027		Absima LiPo 2S 7.6v. 64.60 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 306.0 g. Allowed: 291/315 g.	01.01.25
Absima	Absima # AB4150026		Absima LiPo 2S 7.6v. 72.96 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 329.4 g. Allowed: 320/346 g.	01.01.25
Associated Electrics	Reedy Zappers SG6 # 27607		Reedy LiPo 2S 7.6v. 36.48 Wh. 95C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 168.8 g. Allowed: 160/174 g.	01.01.25
Associated Electrics	Reedy Zappers SG6 # 27602		Reedy LiPo 2S 7.6v. 45.60 Wh. 135C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 239.6 g. Allowed: 228/248 g.	01.01.25
Associated Electrics	Reedy Zappers SG6 # 27603		Reedy LiPo 2S 7.6v. 48.64 Wh. 95C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 221.7 g. Allowed: 212/230 g.	01.01.25
Associated Electrics	Reedy Zappers SG6 # 27600		Reedy LiPo 2S 7.6v. 62.32 Wh. 135C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 325.4 g. Allowed: 314/340 g.	01.01.25
Hoomark	Zombie # H4500US		Hoomark LiPo 2S 7.6v. 34.20 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 153.2 g. Allowed: 146/158 g.	01.01.25
Hoomark	Zombie # H4700LS		Hoomark LiPo 2S 7.6v. 35.72 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 165.6 g. Allowed: 158/172 g.	01.01.25
Hoomark	Zombie # H6200U		Hoomark LiPo 2S 7.6v. 47.12 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 238.5 g. Allowed: 228/247 g.	01.01.25
Hoomark	Zombie # H6400S		Hoomark LiPo 2S 7.6v. 48.64 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.6 g. Allowed: 208/226 g.	01.01.25
Hoomark	Zombie # H6900L		Hoomark LiPo 2S 7.6v. 52.44 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 284.9 g. Allowed: 274/296 g.	01.01.25
Ruddog Distribution	Ruddog # RP-0795		Ruddog LiPo 2S 7.4v. 32.56 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 216.2 g. Allowed: 208/226 g.	01.01.25
Ruddog Distribution	Ruddog # RP-0796		Ruddog LiPo 2S 7.4v. 42.18 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 233.1 g. Allowed: 225/243 g.	01.01.25













Ruddog Distribution	Ruddog # RP-0797		Ruddog LiPo 2S 7.4v. 45.88 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 281.7 g. Allowed: 271/293 g.	01.01.25
Ruddog Distribution	Ruddog # RP-0799		Ruddog LiPo 2S 7.6v. 53.20 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 250.6 g. Allowed: 240/260 g.	01.01.25
Ruddog Distribution	Ruddog # RP-0798		Ruddog LiPo 2S 7.6v. 58.52 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 294.9 g. Allowed: 283/307 g.	01.01.25
Schumacher Racing	Aerox Elite V2 # AX050		Schumacher LiPo 2S 7.4v. 31.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 165.9 g. Allowed: 157/171 g.	01.01.25
Schumacher Racing	Aerox Elite V2 # AX051		Schumacher LiPo 2S 7.4v. 37.0 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.4 g. Allowed: 216/234 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA392S145		Cayote LiPo 2S 7.6v. 29.64 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 137.7 g. Allowed: 132/143 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA462S145		Cayote LiPo 2S 7.6v. 34.96 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 163.9 g. Allowed: 157/170 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA502S145		Cayote LiPo 2S 7.6v. 38.00 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 174.9 g. Allowed: 168/182 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA532S145		Cayote LiPo 2S 7.6v. 40.28 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 207.3 g. Allowed: 199/215 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA552S145		Cayote LiPo 2S 7.6v. 41.8 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 206.2 g. Allowed: 198/214 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA632S145		Cayote LiPo 2S 7.6v. 47.88 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 230.4 g. Allowed: 221/240 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA652S145		Cayote LiPo 2S 7.6v. 49.4 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 226.3 g. Allowed: 217/235 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA682S145		Cayote LiPo 2S 7.6v. 51.68 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 242.7 g. Allowed: 233/252 g.	01.01.25
Shenzhen Cayote Technology	Cayote # CA702S145		Cayote LiPo 2S 7.6v. 53.2 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.4 g. Allowed: 262/284 g.	01.01.25

Shenzhen Cayote Technology	Cayote # CA922S145		Cayote LiPo 2S 7.6v. 69.92 Wh. 145C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 327.9 g. Allowed: 314/341 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA4400 2S14S5		GensAce LiPo 2S 7.6v. 33.44 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 158.8 g. Allowed: 154/166 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA5000 2S14S5		GensAce LiPo 2S 7.6v. 38.0 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 179.3 g. Allowed: 172/186 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA5100 2S14M5		GensAce LiPo 2S 7.6v. 38.76 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 186.4 g. Allowed: 183/199 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA6200 2S14M5		GensAce LiPo 2S 7.6v. 47.12 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 226.4 g. Allowed: 218/236 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA6500 2S14S5		GensAce LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 225.7 g. Allowed: 221/239 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA6600 2S14D5		GensAce LiPo 2S 7.6v. 50.16 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 240.5 g. Allowed: 234/254 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA6800 2S14D5		GensAce LiPo 2S 7.6v. 51.68 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 279.7 g. Allowed: 270/292 g.	01.01.25
Shenzhen Grepow	GensAce Redline 2.0 # GEA7000 2S14M5		GensAce LiPo 2S 7.6v. 53.2 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 249.6 g. Allowed: 240/260 g.	01.01.25
Team EAM	EAM # EAM53130-2		EAM LiPo 2S 7.4v. 39.22 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 193.5 g. Allowed: 184/200 g.	01.01.25
Team EAM	EAM # EAM60140-2S		EAM LiPo 2S 7.4v. 44.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 242.5 g. Allowed: 230/250 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3201		Exalt LiPo 2S 7.4v. 32.56 Wh. 150C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 214.1 g. Allowed: 211/229 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3212		Exalt LiPo 2S 7.6v. 38.8 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 201.6 g. Allowed: 194/210 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3203		Exalt LiPo 2S 7.6v. 39.52 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 182.0 g. Allowed: 169/183 g.	01.01.25















Team Exalt	Exalt X Rated # EXA3202		Exalt LiPo 2S 7.4v. 42.18 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 221.0 g. Allowed: 218/236 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3205		Exalt LiPo 2S 7.4v. 43.66 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 240.6 g. Allowed: 230/250 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3211		Exalt LiPo 2S 7.6v. 48.64 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 225.3 g. Allowed: 217/235 g.	01.01.25
Team Exalt	Exalt X Rated # EXA3207		Exalt LiPo 2S 7.4v. 60.68 Wh. 135C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 333.6 g. Allowed: 319/345 g.	01.01.25
ABM RC	ABM # ABM20010		ABM LiPo 2S 7.6v. 33.44 Wh. 140C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 153.4 g. Allowed: 148/160 g.	01.01.25
ABM RC	ABM # ABM20012		ABM LiPo 2S 7.6v. 36.48 Wh. 140C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 178.7 g. Allowed: 173/187 g.	01.01.25

BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2024 AND ARE ALLOWED AT 2026 EVENTS.








Intellect Pioneering Battery Technology	IP # BL2S4400MC3		Intellect LiPo 2S 7.6v. 34.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 152.8 g. Allowed: 146/158 g.	01.01.24
Intellect Pioneering Battery Technology	IP # BL2S4800MC3		Intellect LiPo 2S 7.6v. 37.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 165.9 g. Allowed: 158/172 g.	01.01.24
Intellect Pioneering Battery Technology	IP # BT2S5000MC3		Intellect LiPo 2S 7.6v. 38.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 204.6 g. Allowed: 197/213 g.	01.01.24
Intellect Pioneering Battery Technology	IP # CM2S5900MC3		Intellect LiPo 2S 7.6v. 45.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 239.7 g. Allowed: 235/255 g.	01.01.24
Intellect Pioneering Battery Technology	IP # CM2S6000MC3		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 271.5 g. Allowed: 259/281 g.	01.01.24
Intellect Pioneering Battery Technology	IP # BT2S6400MC3		Intellect LiPo 2S 7.6v. 49.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.8 g. Allowed: 211/229 g.	01.01.24
Intellect Pioneering Battery Technology	IP # CM2S7000MC3		Intellect LiPo 2S 7.6v. 54.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 289.2 g. Allowed: 274/296 g.	01.01.24
Intellect Pioneering Battery Technology	IP # CT2S8400MC3		Intellect LiPo 2S 7.6v. 64.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 326.1 g. Allowed: 307/333 g.	01.01.24

Intellect Pioneering Battery Technology	IP # CT2S10000MC3		Intellect LiPo 2S 7.6v. 76.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 327.1 g. Allowed: 309/335 g.	01.01.24
Italtrading	EZ-Power # EZP4400/2- SHORT		Ital LiPo 2S 7.6v. 33.44 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 164.1 g. Allowed: 158/172 g.	01.01.24
Italtrading	EZ-Power # EZP5000/2- SHORT		Ital LiPo 2S 7.6v. 38.0 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.8 g. Allowed: 197/213 g.	01.01.24
Italtrading	EZ-Power # EZP6300/2- SHORT		Ital LiPo 2S 7.6v. 47.88 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.7 g. Allowed: 211/229 g.	01.01.24
Italtrading	EZ-Power # EZP7700/2		Ital LiPo 2S 7.6v. 58.52 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 297.3 g. Allowed: 288/312 g.	01.01.24
Italtrading	EZ-Power # EZP9300/2		Ital LiPo 2S 7.6v. 70.68 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 323.7 g. Allowed: 309/335 g.	01.01.24
Team Corally	Corally Voltax # 49705		Corally LiPo 2S 7.4v. 47.4Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 197.4 g. Allowed: 197/213 g.	01.01.24
Team Corally	Corally Voltax # 49724		Corally LiPo 2S 7.4v. 71.0 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 317.4 g. Allowed: 307/333 g.	01.01.24
Kiel Technology	Fido ECP plus # Fi50135-2S1P HV		Kiel LiPo 2S 7.6v. 38.0 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 175.7 g. Allowed: 169/183 g.	01.01.24
Kiel Technology	Fido ECP plus # Fi63130-2S2P HV		Kiel LiPo 2S 7.6v. 47.88 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 230.9 g. Allowed: 222/240 g.	01.01.24
Kiel Technology	Fido ECP plus # Fi76130-2S2P HV		Kiel LiPo 2S 7.6v. 57.8 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 302.9 g. Allowed: 292/316 g.	01.01.24
Kiel Technology	Fido # Fi100130-2S2P HV		Kiel LiPo 2S 7.6v. 76.0 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 313.4 g. Allowed: 301/327 g.	01.01.24
LRP	LRP G4.1 LCG Ultra # 432282		LRP LiPo 2S 7.6v. 49.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 232.3 g. Allowed: 228/246 g.	01.01.24
Nosram	Nosram G4 HV Stock Spec. # 999650		Nosram LiPo 2S 7.6v. 31.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 187.3 g. Allowed: 180/196 g.	01.01.24

Nosram	Nosram G4 HV Stock Spec. # 999651		Nosram LiPo 2S 7.6v. 37.2 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 210.1 g. Allowed: 202/218 g.	01.01.24
Nosram	Nosram G4.1 HV LCG Stock Spec. # 999746		Nosram LiPo 2S 7.6v. 38.7 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 236.6 g. Allowed: 232/252 g.	01.01.24
Nosram	Nosram G4 HV LCG Stock Spec. # 999655		Nosram LiPo 2S 7.6v. 46.4 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 274.8 g. Allowed: 262/284 g.	01.01.24
Nosram	Nosram G4.1 HV LCG Modified # 999758		Nosram LiPo 2S 7.6v. 49.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 234.4 g. Allowed: 228/246 g.	01.01.24
ONYX Power Systems	Modified V2 # OPS46203		ONYX LiPo 2S 7.4v. 34.4 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 214.2 g. Allowed: 206/224 g.	01.01.24
ONYX Power Systems	Modified V2 # OPS65204		ONYX LiPo 2S 7.6v. 49.8 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 216.5 g. Allowed: 206/224 g.	01.01.24
ONYX Power Systems	Modified V2 # OPS100210		ONYX LiPo 2S 7.6v. 76.0 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 324.8 g. Allowed: 307/333 g.	01.01.24
Process Measurement & Analysis	Optipower # OPR 56002S135B		Optipower LiPo 2S 7.4v. 41.44 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 242.8 g. Allowed: 234/254 g.	01.01.24
Process Measurement & Analysis	Optipower # OPR 66002S135B		Optipower LiPo 2S 7.6v. 50.16 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 267.0 g. Allowed: 257/279 g.	01.01.24
Process Measurement & Analysis	Optipower # OPR 95002S135B		Optipower LiPo 2S 7.6v. 72.20 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 310.7 g. Allowed: 300/324 g.	01.01.24
Ruddog Distribution	Ruddog # RP-0752		Ruddog LiPo 2S 7.6v. 39.52 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 194.7 g. Allowed: 187/203 g.	01.01.24
Ruddog Distribution	Ruddog # RP-0725		Ruddog LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 215.5 g. Allowed: 206/224 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX039		Schumacher LiPo 2S 7.4v. 33.3 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 216.5 g. Allowed: 209/227 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX038		Schumacher LiPo 2S 7.4v. 35.5 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 178.8 g. Allowed: 170/184 g.	01.01.24



Schumacher Racing	Aerox Elite V1 # AX041		Schumacher LiPo 2S 7.4v. 38.5 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 236.4 g. Allowed: 230/250 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX043		Schumacher LiPo 2S 7.4v. 41.4 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 222.4 g. Allowed: 216/234 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX044		Schumacher LiPo 2S 7.4v. 43.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 242.3 g. Allowed: 229/249 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX040		Schumacher LiPo 2S 7.6v. 47.9 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 284.9 g. Allowed: 267/289 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX042		Schumacher LiPo 2S 7.4v. 48.1 Wh. 150C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 287.2 g. Allowed: 267/289 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX045		Schumacher LiPo 2S 7.4v. 60.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 318.6 g. Allowed: 298/322 g.	01.01.24
Schumacher Racing	Aerox Elite V1 # AX046		Schumacher LiPo 2S 7.6v. 72.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 322.2 g. Allowed: 305/331 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA382S140		Cayote LiPo 2S 7.4v. 28.1 Wh. 140C Max charge rate: 1C 4 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 127.6 g. Allowed: 123/133 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA442S140		Cayote LiPo 2S 7.4v. 32.6 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 159.5 g. Allowed: 152/164 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA522S140		Cayote LiPo 2S 7.4v. 38.5 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 203.6 g. Allowed: 196/212 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA602S140		Cayote LiPo 2S 7.4v. 44.4 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 228.1 g. Allowed: 221/239 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA652S140		Cayote LiPo 2S 7.4v. 48.1 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 223.0 g. Allowed: 214/232 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA842S140		Cayote LiPo 2S 7.4v. 62.2 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 301.5 g. Allowed: 289/313 g.	01.01.24
Shenzhen Cayote Technology	Cayote # CA952S140		Cayote LiPo 2S 7.4v. 70.3 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 323.2 g. Allowed: 309/335 g.	01.01.24

Shenzhen Grepow	GensAce Redline 2.0 # GEA4200 2S14D5		GensAce LiPo 2S 7.6v. 31.92 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 156.2 g. Allowed: 154/166 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA5000 2S14D5		GensAce LiPo 2S 7.4v. 37.0 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 224.0 g. Allowed: 216/234 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA5300 2S14D5		GensAce LiPo 2S 7.6v. 40.28 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 200.0 g. Allowed: 192/208 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA6000 2S14D5		GensAce LiPo 2S 7.6v. 45.6 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.7 g. Allowed: 211/229 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA6100 2S14D5		GensAce LiPo 2S 7.6v. 46.36 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 226.7 g. Allowed: 221/239 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA6500 2S14D5		GensAce LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 264.2 g. Allowed: 254/276 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA8500 2S14D5		GensAce LiPo 2S 7.6v. 64.6 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 302.9 g. Allowed: 293/317 g.	01.01.24
Shenzhen Grepow	GensAce Redline 2.0 # GEA9600 2S14D5		GensAce LiPo 2S 7.6v. 72.96 Wh. 140C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 324.6 g. Allowed: 312/338 g.	01.01.24
Team EAM	EAM # EAM42130-2		EAM LiPo 2S 7.4v. 31.08 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 165.1 g. Allowed: 156/170 g.	01.01.24
Team EAM	EAM # EAM46200-2		EAM LiPo 2S 7.4v. 34.04 Wh. 200C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 214.8 g. Allowed: 209/227 g.	01.01.24
Team EAM	EAM # EAM50160-2S		EAM LiPo 2S 7.4v. 37.00 Wh. 160C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 225.9 g. Allowed: 219/237 g.	01.01.24
Team EAM	EAM # EAM63140-2		EAM LiPo 2S 7.4v. 46.62 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 279.2 g. Allowed: 273/295 g.	01.01.24
Team EAM	EAM # EAM84130-2		EAM LiPo 2S 7.4v. 62.16 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 327.9 g. Allowed: 315/341 g.	01.01.24
Xiamen 3-Circles	Sunpadow Platin # JA0040H		3-Circles LiPo 2S 7.6v. 34.96 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 170.3 g. Allowed: 164/177 g.	01.01.24 New Wt. See also 2023

Xiamen 3-Circles	Sunpadow Platin # JA0038		3-Circles LiPo 2S 7.4v. 47.36 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 253.7 g. Allowed: 244/264 g.	01.01.24 New Wt. See also 2023
Xiamen 3-Circles	Sunpadow Platin # JA0035H		3-Circles LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 212.4 g. Allowed: 204/221 g.	01.01.24 New Wt. See also 2023
Xiamen 3-Circles	Sunpadow Platin # JA0025H		3-Circles LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 247.9 g. Allowed: 237/257 g.	01.01.24
Xiamen 3-Circles	Sunpadow Platin # JA0037H		3-Circles LiPo 2S 7.6v. 53.2 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 257.4 g. Allowed: 248/268 g.	01.01.24 New Wt. See also 2023
Xiamen 3-Circles	Sunpadow Platin # JA0022H		3-Circles LiPo 2S 7.6v. 74.48 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 319.4 g. Allowed: 306/332 g.	01.01.24 New Wt. See also 2023
DXF	DXF # NGP8000/1		DXF LiPo 2S 7.4v. 59.2 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 309.5 g. Allowed: 306/332 g.	01.01.24
DXF	DXF # NGP8400-HV01		DXF LiPo 2S 7.6v. 63.84 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 306.1 g. Allowed: 297/321 g.	01.01.24

BATTERIES BELOW THIS LEVEL WERE APPROVED BY EFRA FOR 2023 AND ARE ALLOWED AT 2026 EVENTS.

Associated Electrics	Reedy Zappers SG5 # 27396		Reedy LiPo 2S 7.6v. 36.48 Wh. 90C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 164.9 g. Allowed: 158/172 g.	02.01.23
Kiel Technology	Fyrrework ECP plus # F63130-2S2P HV		Kiel LiPo 2S 7.6v. 47.8 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 219.9 g. Allowed: 210/228 g.	02.01.23
Kiel Technology	Fyrrework ECP plus # F66220-2S2P HV		Kiel LiPo 2S 7.6v. 50.1 Wh. 220C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.1 g. Allowed: 262/284 g.	02.01.23
Kiel Technology	Fyrrework ECP plus # F90130-2S2P HV		Kiel LiPo 2S 7.6v. 68.4 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 317.9 g. Allowed: 305/331 g.	02.01.23
LRP	LRP G4.1 LCG Stock Spec # 432287		LRP LiPo 2S 7.6v. 28.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 157.8 g. Allowed: 149/161 g.	02.01.23
LRP	LRP G4.1 LCG Stock Spec # 432283		LRP LiPo 2S 7.6v. 35.0 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 217.8 g. Allowed: 210/228 g.	02.01.23 Allowed Wt. amended 01.01.25
LRP	LRP G4.1 HV Modified # 432263		LRP LiPo 2S 7.6v. 53.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 262.2 g. Allowed: 251/271 g.	02.01.23

Nosram	Nosram G4.1 HV Stock Spec. # 999743		Nosram LiPo 2S 7.6v. 28.1 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 158.1 g. Allowed: 149/161 g.	02.01.23
Nosram	Nosram G4.1 HV Stock Spec. # 999748		Nosram LiPo 2S 7.6v. 35.0 Wh. 135C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 218.5 g. Allowed: 210/228 g.	02.01.23 Allowed Wt. amended 01.01.25
Nosram	Nosram G4.1 HV Modified # 999749		Nosram LiPo 2S 7.6v. 53.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 262.6 g. Allowed: 251/271 g.	02.01.23
Premium RC	Corsatec # CT10014		Corsatec LiPo 2S 7.6v. 74.5 Wh. 138C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 307.2 g. Allowed: 298/322 g.	02.01.23
Ruddog Dist.	Ruddog # RP-0678		Ruddog LiPo 2S 7.6v. 34.4 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 159.5 g. Allowed: 153/165 g.	02.01.23
Ruddog Dist.	Ruddog # RP-0679		Ruddog LiPo 2S 7.6v. 47.9 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 215.3 g. Allowed: 206/224 g.	02.01.23
Ruddog Dist.	Ruddog # RP-0680		Ruddog LiPo 2S 7.6v. 47.1 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 240.1 g. Allowed: 230/250 g.	02.01.23
Ruddog Dist.	Ruddog # RP-0681		Ruddog LiPo 2S 7.6v. 50.2 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 273.0 g. Allowed: 262/284 g.	02.01.23
Ruddog Dist.	Ruddog # RP-0682		Ruddog LiPo 2S 7.6v. 68.4 Wh. 150C Max charge rate: 2C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 316.4 g. Allowed: 303/329 g.	02.01.23
Xiamen 3-Circles	Sunpadow Platin # JA0040H		3-Circles LiPo 2S 7.6v. 34.96 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 174.6 g. Allowed: 166/180 g.	02.01.23
Xiamen 3-Circles	Sunpadow Platin # JA0038		3-Circles LiPo 2S 7.4v. 47.36 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 261.6 g. Allowed: 250/270 g.	02.01.23
Xiamen 3-Circles	Sunpadow Platin # JA0035H		3-Circles LiPo 2S 7.6v. 49.4 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 215.0 g. Allowed: 205/223 g.	02.01.23
Xiamen 3-Circles	Sunpadow Platin # JA0037H		3-Circles LiPo 2S 7.6v. 53.2 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 261.9 g. Allowed: 251/271 g.	02.01.23
Xiamen 3-Circles	Sunpadow Platin # JA0022H		3-Circles LiPo 2S 7.6v. 74.48 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 325.1 g. Allowed: 312/338 g.	02.01.23

Miniz Racing	Marka # MRK- LI4200HV-2S		Miniz Racing LiPo 2S 7.6v. 31.92 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 164.2 g. Allowed: 154/166 g.	02.01.23
Miniz Racing	Marka # MRK- LI6600HV-2S		Miniz Racing LiPo 2S 7.6v. 50.16 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 252.4 g. Allowed: 240/260 g.	02.01.23
Shenzhen Grepow	GensAce Redline # GEA5000 2S13D5		GensAce LiPo 2S 7.4v. 37.0 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Sample complies with EFRA dimensions. Weights:- Sample: 220.0 g. Allowed: 206/224 g.	02.01.23
Paul Worsley, (EFRA Battery Homologation Officer). Updated - 01.01.26. (Nineteen Pages).					