

EUROPEAN FEDERATION RADIO CONTROLLED AUTOMOBILES.

BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.

Lithium based (LiPo) batteries detailed below, are approved for various EFRA Electric Classes. Section Rules will detail the type applicable.

EFRA rules limit battery energy capacity to comply with Airline Requirements (currently 100Wh.), based on Manufacturers data below.

Batteries approved from 2011 onwards must comply with the weight range specified. Batteries factory sealed (glue, weld etc.).















Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed.








Manufacturers advise that charge rate be restricted to 1C for optimum lifespan, but should not be more than stated below (for 2017 on).















Batteries MUST be charged using a 2S LiPo compatible charger. LiPo 'Sack' must be used when charging or discharging prior to race.















It is strictly NOT ALLOWED, to charge 2S LiPo Batteries to give an output voltage exceeding 8.40v.

| Submitted by: | Label Details Part # | Illustration only | Manufacturer Supplied Data. | EFRA measured Specification, | Approval Date |
|--|------------------------------|---|---|---|---------------|
| NO 'SADDLE' BATTERIES HAVE BEEN SUBMITTED FOR HOMOLOGATION DURING 2018 - 2026. | | | | | |
| BATTERIES ON THIS LIST WERE APPROVED BY EFRA IN YEARS 2009 - 2017 AND ARE ALLOWED AT 2026 EVENTS. | | | | | |
| Intellect Battery | IP # TP2S6000HV2 |  | Intellect LiPo 2S 2 x 3.8v. 2 x 23.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes | Sample complies with EFRA dimensions. Weights:- Sample: Pr. 273.9 g. Allowed: 261/283 g. | 05.01.17 |
| Team Corally | Corally Coral-X # 48374 |  | Corally LiPo 2S 2 x 3.8v. 2 x 22.8 Wh. 100C Max charge rate:1.2C 4 mm. Tubes | Sample complies with EFRA dimensions. Weights:- Sample: Pr. 276.7 g. Allowed: 265/287 g. | 05.01.17 |
| LRP | LRP # 430240 |  | LRP LiPo 2S 7.4v. 42.9 Wh. 110C Wt. 263/285 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 273.9 g. | 14.01.16 |
| LRP | LRP # 430242 |  | LRP LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 196/212 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 204.5 g. | 14.01.16 |
| LRP | LRP # 430241 |  | LRP LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 181/196 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 188.6 g. | 14.01.16 |
| LRP | LRP # 430243 |  | LRP LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 202/218 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 211.3 g. | 14.01.16 |
| Neidhart SA | Orion # ORI 14085 |  | Orion LiPo 2S 7.4v. 29.6 Wh. 110C Wt. 184/198 g. 4 mm. Tubes | Sample complies with EFRA dimensions. Sample Wt. 193.7 g. | 14.01.16 |
| Nosram | Nosram X-treme Race # 999533 |  | Nosram LiPo 2S 7.4v. 42.9 Wh. 110C Wt. 263/285 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 273.4 g. | 14.01.16 |
| Nosram | Nosram X-treme Race # 999535 |  | Nosram LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 196/212 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 204.9 g. | 14.01.16 |
| Nosram | Nosram X-treme Race # 999534 |  | Nosram LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 181/196 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 189.9 g. | 14.01.16 |













| | | | | | |
|--------------------------------------|--|---|---|---|----------|
| Nosram | Nosram X-treme Race # 999536 |  | Nosram LiPo 2S 7.4v. 28.9 Wh. 110C Wt. 202/218 g. 5 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 211.1 g. | 14.01.16 |
| RC Concept | Omega # 50C5157200T |  | RC Concept LiPo 2S 7.4v. 42.2 Wh. 100C Wt. 267/289 g. 4 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 278.4 g. | 14.01.16 |
| Revell GmbH | TrakPower # TKPC0725 |  | TrakPower LiPo 2S 7.4v. 19.0 Wh. X 2 100C Wt. 267/289 g. 4 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 275.5 g. | 14.01.16 |
| Shenzhen Grepow | GensAce # B60C57002S3P H/Case 26 |  | GensAce LiPo 2S 7.4v. 42.2 Wh. 60C Wt. 274/296 g. 4 mm. Tubes | Sample complies with EFRA dimensions. Sample Wt. 276.6 g. | 14.01.16 |
| MaxTime | MTB # MTB293 |  | Maxtime LiPo 2S 7.4v. 42.2 Wh. 100C Wt. 278/302 g. 4 mm. Tubes. | Sample complies with EFRA dimensions. Sample Wt. 293.3 g. | 14.01.16 |
| Intellect Battery | IP # TP2S6000SV1 |  | Intellect LiPo 2S 7.4v. 22.0 (x2) Wh. 100C Wt. 267/289 g. | Sample complies with EFRA dimensions. Sample Wt. 278.9 g. | 08.01.15 |
| LRP | LRP # 430225 |  | LRP LiPo 2S 7.4v. 40.7 Wh. 110C Wt. 265/287 g. | Sample complies with EFRA dimensions. Sample Wt. 277.5 g. | 08.01.15 |
| LRP | LRP # 430226 |  | LRP LiPo 2S 7.4v. 27.4 Wh. 110C Wt. 180/196 g. | Sample complies with EFRA dimensions. Sample Wt. 190.3 g. | 08.01.15 |
| Modern Creations | Team Silverback SpiralX # 6100902SSP |  | Modern Creations LiPo 2S 7.4v. 45.1 Wh. 90C Wt. 254/276 g. | Sample complies with EFRA dimensions. Sample Wt. 267.0 g. | 08.01.15 |
| Muchmore Racing | Impact # MLI-IS6000FD2 |  | Muchmore LiPo 2S 7.4v. 44.4 Wh. 90C Wt. 267/289 g. | Sample complies with EFRA dimensions. Sample Wt. 278.1 g. | 08.01.15 |
| Nosram | Nosram X-treme Race # 999519 |  | Nosram LiPo 2S 7.4v. 40.7 Wh. 110C Wt. 265/287 g. | Sample complies with EFRA dimensions. Sample Wt. 274.9 g. | 08.01.15 |
| Nosram | Nosram X-treme Race # 999520 |  | Nosram LiPo 2S 7.4v. 27.4 Wh. 110C Wt. 180/196 g. | Sample complies with EFRA dimensions. Sample Wt. 189.7 g. | 08.01.15 |
| Process Measurement & Analysis | Optipower # OPR500050BSD |  | Optipower LiPo 2S 7.4v. 37.0 Wh. 50C Wt. 271/293 g. | Sample complies with EFRA dimensions. Sample Wt. 281.7 g. | 08.01.15 |
| Process Measurement & Analysis | Optipower # OPR500050FLSD |  | Optipower LiPo 2S 7.4v. 37.0 Wh. 50C Wt. w/wire 280/304 g. | Sample complies with EFRA dimensions. Sample Wt. 291.8 g. | 08.01.15 |

| | | | | | |
|-----------------------|--|---|--|---|----------|
| Pro Models Corally | Corally # 48279 |  | Pro Models LiPo 2S 7.4v. 40.7 Wh. 100C Wt. 283/307 g. | Sample complies with EFRA dimensions. Sample Wt. 290.3 g. | 08.01.15 |
| ProTek RC | ProTek RC # PTK 5112-15 |  | ProTek LiPo 2S 7.4v. 38.5 Wh. 100C Wt. 267/289 g. | Sample complies with EFRA dimensions. Sample Wt. 278.1 g. | 08.01.15 |
| Ruddog Dist. | Vampire # VR-1029 |  | Vampire LiPo 2S 7.4v. 42.2 Wh. 80C Wt. 278/302 g. | Sample complies with EFRA dimensions. Sample Wt. 291.0 g. | 08.01.15 |
| CS- Electronic | CS Professional # C211033 |  | CS LiPo 2S 7.4v. 44.4 Wh. 80C Wt. 267/289 g. | Sample complies with EFRA dimensions. Wt. 279.9 g. | 05.01.14 |
| Hacker Motor | Hacker Top Fuel # 75700278 |  | Hacker LiPo 2S 7.4v. 40.7 Wh. 90C Wt. 277/300 g. | Sample complies with EFRA dimensions. Wt. 288.2 g. | 05.01.14 |
| Hobbico RC | TrakPower # TKPC0625 |  | TrakPower LiPo 2S 7.4v. 22 (x2) Wh. 90C Wt. 267/289 g. | Sample complies with EFRA dimensions. Wt. 278.5 g. | 05.01.14 |
| VTEC LRP | VTEC # 430213 |  | LRP LiPo 2S 7.4v. 42.9 Wh. 55C Wt. 267/289 g. | Sample complies with EFRA dimensions. Wt. 279.4 g. | 05.01.14 |
| Muchmore Racing | Muchmore Impact # MLI- IS5000FD |  | Muchmore LiPo 2S 7.4v. 37.0 Wh. 50C Wt. 245/265 g. | Sample complies with EFRA dimensions. Wt. 254.6 g. | 05.01.14 |
| Neidhart SA | ORION Carbon Pro # ORI 14063 |  | Orion LiPo 2S 7.4v. 40.7 Wh. 100C Wt. 276/3300 g. | Sample complies with EFRA dimensions. Wt. 288.1 g. | 05.01.14 |
| Neidhart SA | ORION Carbon Pro # ORI 14064 |  | Orion LiPo 2S 7.4v. 40.7 Wh. 100C Wt. w/wire 296/320 g. | Sample complies with EFRA dimensions. Wt. w/wire 307.7 g. | 05.01.14 |
| VTEC Nosram | Nosram X-treme Race # 999510 |  | Nosram LiPo 2S 7.4v. 42.9 Wh. 55C Wt. 267/289 g. | Sample complies with EFRA dimensions. Wt. 279.4 g. | 05.01.14 |
| Pro Models BVBA | Corally # 48260 |  | Corally LiPo 2S 7.4v. 42.9 Wh. 90C Wt. 264/286 g. | Sample complies with EFRA dimensions. Wt. 266.3 g. | 05.01.14 |
| ProTek RC | ProTek RC # PTK LPH 2S100 SP |  | ProTek LiPo 2S 7.4v. 40.7 Wh. 100C Wt. 274/296 g. | Sample complies with EFRA dimensions. Wt. 282.1 g. | 05.01.14 |
| Tianco | ORCA Infinite # OB6090SP |  | Orca LiPo 2S 7.4v. 22.2 (x2) Wh. 90C Wt. 269/291 g. | Sample complies with EFRA dimensions. Wt. 283.3 g. | 05.01.14 |












| | | | | | |
|-----------------------------|--|---|---|--|----------|
| Trinity Revtech Epic | RevTech FormulaX # REV2023-5 |  | Revtech LiPo 2S 7.4v. 46.25 Wh. 100C Wt. 260/282 g. 5mm. Tubes | Sample complies with EFRA dimensions. Wt. 270.8 g. | 05.01.14 |
| Xcite RC | Xcite Energy XXL # 56600106 |  | Xcite LiPo 2S 7.4v. 44.4 Wh. 80C Wt. 274/296 g. | Sample complies with EFRA dimensions. Wt. 279.2 g. | 05.01.14 |
| Italtrading | EZ-Power # EZP6000/1+1 |  | Ital LiPo 2S 7.4v. 44.4 Wh. 60C Wt. 267/289 g. | Sample complies with EFRA dimensions. Wt. 277.4 g. | 05.01.14 |
| nVision | nVision # NVO 1122 |  | nVision LiPo 2S 7.4v. 40.7 Wh. 100C Wt. 274/296 g. | Sample complies with EFRA dimensions. Wt. 284.6 g. | 05.01.14 |
| nVision | nVision # NVO 1123 |  | nVision LiPo 2S 7.4v. 40.7 Wh. 100C Wt. w/wire 282/306 g. | Sample complies with EFRA dimensions. Wt. w/wire 293.2 g. | 05.01.14 |
| RC Industries Int. | Pro Amps # PA60552SSA |  | Pro Amps LiPo 2S 7.4v. 40.7 Wh. 60C Wt. 252/274 g. | Sample complies with EFRA dimensions. Wt. 262.1 g. | 05.01.14 |
| Shanghai Dualsky | Track & Field # 33864 |  | Dualsky LiPo 2S 7.4v. 39.2 Wh. 70C Wt. 259/281 g. | Sample complies with EFRA dimensions. Wt. 270.4 g. | 05.01.14 |
| Shenzhen Acepow Electronics | Gens ace # B50C57002S3 Psaddle12 |  | Acepow LiPo 2S 7.4v. 42.2 Wh. 50C Wt. 274/296 g. | Sample complies with EFRA dimensions. Wt. 285.3 g. | 05.01.14 |
| Arrowind Hobby | Black Magic # BM A35 4802S |  | Arrowind Hobby LiPo 2S 7.4v. 17.76 Wh. (x2) 35C Wt. 242/262 g. Also in Carbon/F finish. | Complies with EFRA. specified dimensions. Wt. 254.3 g. | 02.01.13 |
| Arrowind Hobby | Black Magic # BM A99 5002S |  | Arrowind Hobby LiPo 2S 7.4v. 18.5 Wh. (x2) 99C Wt. 248/268 g. Also in Carbon/F finish. | Complies with EFRA. specified dimensions. Wt. 258.7 g. | 02.01.13 |
| Associated Electrics | Reedy # 310 |  | Reedy LiPo 2S 7.4v. 21.0 Wh. (x2) 65C Wt. 257/278 g. | Complies with EFRA. specified dimensions. Wt. 267.1 g. | 02.01.13 |
| Intellect Battery | IP # TP2S6000V8 |  | Intellect LiPo 2S 7.4v. 22.0 Wh. (x2) 80C Wt. 274/297 g. | Complies with EFRA. specified dimensions. Wt. 286.7 g. | 02.01.13 |
| VTEC | VTEC # 430203 |  | LRP LiPo 2S 7.4v. 42.9 Wh. 55C Wt. 269/291 g. | Complies with EFRA. specified dimensions. Wt. 282.8 g. | 02.01.13 |
| Modern Creations | Team Silverback Venus # 5600752SSP |  | Team Silverback LiPo 2S 7.4v. 41.44 Wh. 75C Wt. 254/275 g. | Complies with EFRA. specified dimensions. Wt. 271.1 g. | 02.01.13 |

| | | | | | |
|-----------------------------------|---|---|--|--|----------|
| VTEC | Nosram X-treme Race # 999503 |  | Nosram LiPo 2S 7.4v. 42.9 Wh. 55C Wt. 269/291 g. | Complies with EFRA. specified dimensions. Wt. 282.8 g. | 02.01.13 |
| Vampire Racing | Vampire # VR-1024 |  | Vampire LiPo 2S 7.4v. 20.0 Wh. (x2) 70C Wt. 278/301 g. | Complies with EFRA. specified dimensions. Has chassis locations Wt. 286.8 g. | 02.01.13 |
| Vapex Technology | VP Racing # VP95088 |  | Vapex LiPo 2S 7.4v. 48.0 Wh. 65C Wt. 280/303 g. | Complies with EFRA. specified dimensions. Wt. 292.0 g. | 02.01.13 |
| Acorn Innovations | Acorn Mad Series # 1611626 |  | Acorn LiPo 2S 7.4v. 20.0 Wh. (x2) 70C Wt. 253/274 g. | Complies with EFRA. specified dimensions. Wt. 264.0 g. | 02.01.13 |
| HUECO Handels | H-Speed # HSP-0010 |  | H-Speed LiPo 2S 7.4v. 41.0 Wh. 60C Wt. 288/312 g. | Complies with EFRA. specified dimensions. Wt. 286.2 g. | 02.01.13 |
| Shanghai Dualsky | Track & Field # 33864 |  | Dualsky LiPo 2S 7.4v. 39.2 Wh. 70C Wt. 259/281 g. | Complies with EFRA. specified dimensions. Wt. 269.2 g. | 02.01.13 |
| Shenzhen Acepow Electronics | Gens ace # B25C51001S3 PS12 |  | Acepow LiPo 2S 7.4v. 18.9 Wh. (x2) 25C Wt. 280/303 g. | Complies with EFRA. specified dimensions. Wt. 289.8 g. | 02.01.13 |
| Advanced Energy | Thunder Power RC # TP5000- 2SPR65S |  | Thunder Power LiPo 2S 7.4v. 37.0 Wh. 65C Wt. 278/302 g. | Length: 138.22 mm. Width: 46.46 mm. High: 25.09 mm. Wt. 288.2 g. | 02.01.12 |
| Hacker Motor | Hacker Top Fuel # 75000278 |  | Hacker LiPo 2S 7.4v. 40.7 Wh. 90C. Wt. 269/291 g. | Length: 138.23 mm. Width: 46.64 mm. High: 24.43 mm. Wt. 281.4 g. | 02.01.12 |
| VTEC | VTEC # 79844 |  | LRP LiPo 2S 7.4v. 41.5 Wh. 55C Wt. 276/298 g. | Length: 137.46 mm. Width: 46.21 mm. High: 24.77 mm. Wt. 276.3 g. Has chassis location. | 02.01.12 |
| VTEC | Nosram X-treme Race # 99941 |  | Nosram LiPo 2S 7.4v. 41.5 Wh. 55C Wt. 276/298 g. | Length: 137.44 mm. Width: 46.26 mm. High: 24.73 mm. Wt. 277.6 g. Has chassis location. | 02.01.12 |
| Robitronic Electronic | Robitronic # RO5246 |  | Robitronic LiPo 2S 7.4v. 37.0 Wh. 70C Wt. 276/299 g. | Length: 137.76 mm. Width: 45.45 mm. High: 24.88 mm. Wt. 288.6 g. | 02.01.12 |
| Shenzhen Acepow Electronics | Gens ace # ACE25- 4800-0203B |  | Acepow LiPo 2S 7.4v. 35.5 Wh. 25C Wt. 269/291 g. | Length: 138.32 mm. Width: 46.79 mm. High: 24.80 mm. Wt. 280.3 g. | 02.01.12 |
| Vapex Technology | VP Racing # VP94449 |  | Vapex LiPo 2S 7.4v. 44.5 Wh. 50C Wt. 290/314 g. | Length: 137.96 mm. Width: 46.07 mm. High: 24.47 mm. Wt. 302.2 g. | 02.01.12 |

| | | | | | |
|---------------------------------|-----------------------------------|---|--|--|----------|
| Associated Electrics | Reedy # 627 |  | Reedy LiPo 2S 7.4v. 5200 mah. 60C Wt. 286/310 g. | Length: 137.92 mm. Width: 46.66 mm. High: 25.08 mm. Wt. 298.5 g. | 02.01.11 |
| Bionic Batteries | Bionic # BCS40- 4800-SAD |  | Bionic LiPo 2S 7.4v. 4800 mah. 40C Wt. 280/304 g. | Length: 137.50 mm. Width: 46.47 mm. High: 23.64 mm. Wt. 291.4 g. | 02.01.11 |
| Bionic Batteries | Bionic # BCS50- 5000-SAD |  | Bionic LiPo 2S 7.4v. 5000 mah. 50C Wt. 288/312 g. | Length: 137.50 mm. Width: 46.37 mm. High: 24.92 mm. Wt. 301.2 g. | 02.01.11 |
| CS- Electronic | CS Professional # C211019 |  | CS LiPo 2S 7.4v. 19.2 Wh x 2 50C Wt. 264/286 g | Length: 137.21 mm. Width: 46.48 mm. High: 24.75 mm. Wt. 268.9 g | 02.01.11 |
| Graupner | GM V-MAXX # 99009 |  | GM LiPo 2S 7.4v. 5600 mah. 60C. Wt. 274/296 g. | Length: 137.43 mm. Width: 46.07 mm. High: 24.68 mm. Wt. 280.5 g. | 02.01.11 |
| Intellect Battery | IP # TP2S5400V6 |  | Intellect LiPo 2S 7.4v. 5400 mah. 60C Wt. 274/296 g | Length: 137.98 mm. Width: 46.24 mm. High: 24.98 mm. Wt. 283.5 g | 02.01.11 |
| Robitronic Electronic | Robitronic # RO5242 |  | Robitronic LiPo 2S 7.4v. 5200 ?? 60C Wt. 284/308 g | Length: 137.46 mm. Width: 46.40 mm. High: 24.71 mm. Wt. 294.8 g | 02.01.11 |
| Superior Matching Concept | SMC C-Max # 5260SP |  | SMC LiPo 2S 7.4v. 5200 mah. 60C Wt. 260/282 g. | Length: 138.74 mm. Width: 46.42 mm. High: 24.36 mm. Wt. 273.4 g. | 02.01.11 |
| Team ORION | ORION Carbon Pro # ORI14048 |  | Orion LiPo 2S 7.4v. 40.7 Wh. 90C Wt. 266/288 g. | Length: 138.10 mm. Width: 46.57 mm. High: 23.73 mm. Wt. 278.0 g. | 02.01.11 |
| Team ORION | ORION Carbon Pro # ORI14049 |  | Orion LiPo 2S 7.4v. 40.7 Wh. 90C Wt. w/wire 297/321 g | Length: 138.51 mm. Width: 46.84 mm. High: 24.52 mm. Wt. w/wire 310.0 g. | 02.01.11 |
| nVision | nVision # NV1102 |  | nVision LiPo 2S 7.4v. 5500 mah. 90C Wt. 266/288 g. | Length: 138.01 mm. Width: 46.66 mm. High: 23.94 mm. Wt. 281.0 g. | 02.01.11 |
| Tianco | ORCA Infinite # OB5235IS |  | Tianco LiPo 2S 7.4v. 5200 mah. 45C Wt. 274/296 g. | Length: 137.41 mm. Width: 46.22 mm. High: 24.95 mm. Wt. 277.3 g. | 02.01.11 |
| Vampire Racing | Vampire # VR-1017 |  | Vampire LiPo 2S 7.4v. 5400 mah. 60C Wt. 274/296 g. | Length: 137.28 mm. Width: 46.15 mm. High: 24.93 mm. Wt. 280.6 g. | 02.01.11 |
| Vapex Tech. | VP # VP93671 |  | Vapex LiPo 2S 7.4v. 5400 mah. 50C Wt. 268/290 g. | Length: 137.84 mm. Width: 46.27 mm. High: 24.92 mm. Wt. 268.3 g. | 02.01.11 |

| | | | | | |
|--------------------------|--|---|---|---|----------|
| RC Plus | Python Plus # RC-PPC40-4800-SAD |  | RC Plus LiPo 2S 7.4v. 4800 mah. 40C Wt. 280/304 g. | Length: 137.69 mm. Width: 46.48 mm. High: 23.80 mm. Wt. 289.2 g. | 02.01.11 |
| RC Plus | Python Plus # RC-PPC50-5000-SAD |  | RC Plus LiPo 2S 7.4v. 5000 mah. 50C Wt. 288/312 g. | Length: 137.69 mm. Width: 46.25 mm. High: 24.83 mm. Wt. 300.6 g. | 02.01.11 |
| Xcelorin | Xcelorin # LOSB9878 |  | SMC LiPo 2S 7.4v. 5200 mah. 60C Wt. 265/287 g. | Length: 138.14 mm. Width: 46.18 mm. High: 24.59 mm. Wt. 272.4 g. | 02.01.11 |
| VTEC | LRP Competition car line. # 79878 |  | LRP LiPo 2S 7.4v. 5000. 50C | Length: 138.74 mm. Width: 46.29 mm. High: 24.83 mm. Wt. 262.8 g Has chassis location. | 17.01.10 |
| ORION | ORION Carbon. # ORI14014 |  | Orion LiPo 2S 7.4v. 4500. 45C | Length: 138.33 mm. Width: 46.66 mm. High: 24.61 mm. Wt. 274.2 g. | 17.01.10 |
| ORION | ORION Carbon # ORI14015 |  | Orion LiPo 2S 7.4v. 4500 45C | Length: 137.80 mm. Width: 46.58 mm. High: 24.91 mm. Wt. inc. wire 300.8 g | 17.01.10 |
| Graupner | GM V-MAXX # 99001 |  | GM LiPo 2S 7.4v. 5200 mah. 35C 1 off tube 3.5mm. Case Black or C/Fibre. | Length: 137.32 mm. Width: 46.16 mm. High: 22.76 mm. Wt. 258.0 g | 17.01.10 |
| Graupner | GM V-MAXX # 98993 |  | GM LiPo 2S 7.4v. 5200 mah. 45C 4.0mm Tubes. Case Black or C/Fibre. | Length: 137.32 mm. Width: 46.27 mm. High: 24.79 mm. Wt. 276.4 g | 17.01.10 |
| Graupner | GM V-MAXX # 98996 |  | GM LiPo 2S 7.4v. 5200 mah. 45C 1 off Tube 3.5mm. Case Black or C/Fibre. | Length: 137.34 mm. Width: 46.28 mm. High: 24.73 mm. Wt. 277.1 g | 17.01.10 |
| Robitronic Electronic | Robitronic # RO5217 |  | Robitronic LiPo 2S 7.4v. 4500. 50C | Length: 137.99 mm. Width: 46.52 mm. High: 23.60 mm. Wt. 273.8 g | 17.01.10 |
| Robitronic Electronic | Robitronic # RO5218 |  | Robitronic LiPo 2S 7.4v. 5000. 50C | Length: 137.61 mm. Width: 46.28 mm. High: 24.97 mm. Wt. 294.6 g | 17.01.10 |
| Associated Electrics | Reedy # 686 |  | Reedy LiPo 2S 7.4v. 4200 mah. 40C | Length: 137.34 mm. Width: 46.94 mm. High: 23.16 mm. Wt. inc. wire 267.6 g | 17.01.10 |
| Desire Power | Desire Power V6 # DPC5000XP40 |  | Desire Power LiPo 2S 7.4v. 5000 mah. 40C | Length: 138.94 mm. Width: 46.41 mm. High: 24.75 mm. Wt. 268.2 g | 17.01.10 |
| Intellect Battery | IP # TP2S5000V3 |  | IP LiPo 2S 7.4v. 5000 mah. 35C | Length: 137.78 mm. Width: 46.30 mm. High: 22.82 mm. Wt. 258.3 g | 17.01.10 |

| | | | | | |
|-------------------|--------------------------------------|---|---|---|----------|
| Intellect Battery | IP # TP2S5200V4 |  | IP LiPo 2S 7.4v. 5200 mah. 45C | Length: 137.44 mm. Width: 46.26 mm. High: 24.80 mm. Wt. 276.2 g | 17.01.10 |
| Muchmore | Impact # MLI-IS5000A |  | Muchmore LiPo 2S 7.4v. 5000 35C | Length: 137.34 mm. Width: 46.20 mm. High: 22.84 mm. Wt. 258.9 g | 17.01.10 |
| Muchmore | Impact # MLI-IS5200B |  | Muchmore LiPo 2S 7.4v. 5200 45C | Length: 137.40 mm. Width: 46.28 mm. High: 24.82 mm. Wt. 275.8 g | 17.01.10 |
| Yuntong | Yuntong # YT90093 |  | Yuntong LiPo 2S 7.4v. 4500 mah. 50C | Length: 137.58 mm. Width: 44.78 mm. High: 23.42 mm. Wt. 273.9 g | 17.01.10 |
| Yuntong | Yuntong # YT90109 |  | Yuntong LiPo 2S 7.4v. 5000 mah. 50C | Length: 137.71 mm. Width: 46.34 mm. High: 24.98 mm. Wt. 295.9 g | 17.01.10 |
| Bionic Batteries | Bionic # BCS40-4500-SAD |  | Bionic LiPo 2S 7.4v. 4500 mah. 40C | Length: 138.62 mm. Width: 46.66 mm. High: 24.58 mm. Wt. 272.0 g | 17.01.10 |
| CS-Electronic | CS-Factory Professional # C211013 |  | CS LiPo 2S 7.4v. 5200 50C | Length: 137.69 mm. Width: 46.27 mm. High: 24.98 mm. Wt. 299.0 g | 17.01.10 |
| VTEC | Nosram X-Treme Race # 99948 |  | Nosram LiPo 2S 7.4v. 5000 50C | Length: 138.96 mm. Width: 46.42 mm. High: 24.85 mm. Wt. 263.4 g Has chassis location | 17.01.10 |
| Moore Speed | Moore-speed # MS-B7405 |  | Moore-speed LiPo 2S 7.4v. 4600 mah. 50C | Length: 138.04 mm. Width: 46.49 mm. High: 24.65 mm. Wt. 273.9 g | 17.01.10 |
| Moore Speed | Moore-speed # MS-B7406 |  | Moore-speed LiPo 2S 7.4v. 4600 mah. 50C | Length: 137.78 mm. Width: 46.49 mm. High: 24.67 mm. Wt. inc. wire 298.7 g | 17.01.10 |
| Vampire Racing | Vampire # VR-1012 |  | Vampire LiPo 2S 7.4v. 4400 mah. 40C | Length: 136.96 mm. Width: 46.06 mm. High: 22.79 mm. Wt. 231.4 g | 17.01.10 |
| Vapex | VP # VP654358SH 30C-3P |  | Vapex LiPo 2S 7.4v. 4500 mah. 30C | Length: 137.09 mm. Width: 46.27 mm. High: 23.70 mm. Wt. 235.9 g | 17.01.10 |
| VTEC | LRP Competition car line. # 79866 |  | LRP LiPo 2S 7.4v. 4800. 40C Saddle Pack | Length: 138.73 mm. Width: 46.09 mm. High: 23.48 mm. Wt. 249.3 g Has chassis location. | 16.02.09 |
| GM Racing | GM V-MAXX # 98994 |  | GM LiPo 2S2P 7.4v. 4200 mah. 30C Saddle Pack | Length: 137.13 mm. Width: 46.14 mm. High: 22.74 mm. Wt. 230.6 g | 16.02.09 |

| | | | | | |
|-----------------------|------------------------|---|---|---|----------|
| GM Racing | GM V-MAXX # 98988 |  | GM LiPo 2S3P 7.4v. 4200 mah. 35C Saddle Pack | Length: 137.08 mm. Width: 46.43 mm. High: 23.36 mm. Wt. inc. wire 279.4 g | 16.02.09 |
| Hyperion HK | Swift #HPSW304200 |  | Swift LiPo 2S 7.4v. 4200 mah. 30C Saddle Pack | Length: 137.15 mm. Width: 46.12 mm. High: 22.80 mm. Wt. 231.5 g | 16.02.09 |
| Robitronic Electronic | Robitronic # RO5213 |  | Robitronic LiPo 2S2P 7.4v. 4600 35C Saddle Pack | Length: 137.60 mm. Width: 44.81 mm. High: 23.30 mm. Wt. 283.0 g | 16.02.09 |
| Robitronic Electronic | Robitronic # RO5214 |  | Robitronic LiPo 2S2P 7.4v. 5000 25C Saddle Pack | Length: 137.31 mm. Width: 44.83 mm. High: 23.37 mm. Wt. 276.0 g | 16.02.09 |
| Speedpower | Speedpower #SLR423HS |  | Speedpower LiPo 2S 7.4v. 4200 mah. 30C Saddle Pack | Length: 137.09 mm. Width: 46.14 mm. High: 23.03 mm. Wt. inc. wire 232.2 g | 16.02.09 |
| TrakPower | TrakPower # TP32002SSP |  | TrakPower LiPo 2S 7.4v. 3200 mah. 20C Also EFRA label. 2009 Revised version | Length: 137.52 mm. Width: 46.87 mm. High: 21.24 mm. Wt. 188.0 g | 16.02.09 |
| Associated Electrics | Reedy # 712 |  | Reedy LiPo 2S 7.4v. 4200 mah. 35C Saddle Pack | Length: 137.62 mm. Width: 46.74 mm. High: 23.22 mm. Wt. inc. wire 283.5 g | 16.02.09 |
| Corally | Corally # 48243 |  | Corally LiPo 2S 7.4v. 4200 mah. 35C Saddle Pack | Length: 137.10 mm. Width: 46.52 mm. High: 23.35 mm. Wt. inc. wire 277.5 g | 16.02.09 |
| Intellect Battery | IP # TP2S4200V1 |  | Intellect LiPo 2S 7.4v. 4200 mah. 30C Saddle Pack | Length: 137.07 mm. Width: 46.08 mm. High: 22.81 mm. Wt. 230.5 g | 16.02.09 |
| Vampire Racing | Vampire # VR-1007 |  | Vampire LiPo 2S 7.4v. 4400 mah. 30C Saddle Pack | Length: 137.07 mm. Width: 46.13 mm. High: 22.81 mm. Wt. 231.2 g | 16.02.09 |
| Yuntong | Yuntong # YT90071 |  | Yuntong LiPo 2S 7.4v. 4600 mah. 35C Saddle Pack | Length: 137.55 mm. Width: 45.00 mm. High: 23.34 mm. Wt. 282.2 g | 16.02.09 |